

SOL002 - VNF Indicator interface

Overview

SOL002 - VNF Indicator interface IMPORTANT: Please note that this file might be not aligned to the current version of the ETSI Group Specification it refers to and has not been approved by the ETSI NFV ISG. In case of discrepancies the published ETSI Group Specification takes precedence. Please report bugs to <https://forge.etsi.org/bugzilla/buglist.cgi?component=Nfv-Openapis>

Version information

Version : 1.2.1-impl:etsi.org:ETSI_NFV_OpenAPI:1

Contact information

Contact : NFV-SOL WG

License information

License : ETSI Forge copyright notice

License URL : <https://forge.etsi.org/etsi-forge-copyright-notice.txt>

Terms of service : null

URI scheme

BasePath : /vnfind/v1

Schemes : HTTP, HTTPS

Consumes

- `application/json`

Produces

- `application/json`

External Docs

Description : ETSI GS NFV-SOL 002 V2.7.1

URL : https://www.etsi.org/deliver/etsi_gs/NFV-SOL/001_099/002/02.07.01_60/gs_nfv-sol002v020701p.pdf

Paths

Retrieve API version information

GET /api_versions

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

| Type | Name | Description | Schema |
|--------|-----------------------------------|--|--------|
| Header | Version <i>optional</i> | Version of the API requested to use when responding to this request. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|---|------------------------------|
| 200 | 200 OK API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version. | Response 200 |

| HTTP Code | Description | Schema |
|-----------|---|--------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 400 |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 413 | <p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 413 |
| 414 | <p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 414 |
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |

| HTTP Code | Description | Schema |
|-----------|--|-------------------------------------|
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 422</p> |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 429</p> |

| HTTP Code | Description | Schema |
|-----------|--|-------------------------------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 500</p> |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 503</p> |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 504</p> |

Response 200

| Name | Description | Schema |
|---------------------------------------|---|--|
| apiVersions <i>required</i> | Version(s) supported for the API signaled by the uriPrefix attribute. | < apiVersions > array |
| uriPrefix <i>required</i> | Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/. | string |

apiVersions

| Name | Description | Schema |
|--|--|--------------------|
| isDeprecated <i>optional</i> | If such information is available, this attribute indicates whether use of the version signaled by the version attribute is deprecated (true) or not (false). A deprecated version is still supported by the API producer but is recommended not to be used any longer. When a version is no longer supported, it does not appear in the response body. | boolean |
| retirementDate <i>optional</i> | Date-time stamp. Representation: String formatted according to IETF RFC 3339. | string (date-time) |
| version <i>required</i> | Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 9.1 (SOL013). | string |

Response 400

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 413

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 414

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Query multiple indicators

GET /indicators

Description

Get a list of indicators. Support of attribute based filtering via query parameters.

Parameters

| Type | Name | Description | Schema |
|---------------|---|--|--------|
| Header | Authorization <i>optional</i> | The authorization token for the request. Reference: IETF RFC 7235 | string |
| Header | Version <i>required</i> | Version of the API requested to use when responding to this request. | string |

| Type | Name | Description | Schema |
|-------|--|---|--------|
| Query | filter <i>optional</i> | Attribute-based filtering expression according to clause 5.2 of ETSI GS NFV-SOL 013. The VNFM shall support receiving this parameter as part of the URI query string. The EM/VNF may supply this parameter. The VNF may supply its instance Id as an attribute filter. All attribute names that appear in the VnfIndicator data type and in data types referenced from it shall be supported by the VNFM in the filter expression. If receiving, this parameter is not supported a 400 Bad Request response shall be returned (See table 8.4.2.3.2-2). EXAMPLE objects obj1: {"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]} obj2: {"id":456, "weight":500, "parts":[{"id":3, "color":"green"}, {"id":4, "color":"blue"}]} Request 1: GET .../container Response 1: [{"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]}, {"id":456, "weight":500, "parts":[{"id":3, "color":"green"}, {"id":4, "color":"blue"}]}] Request 2: GET .../container?filter=(eq.weight,100) Response 2: [{"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]}] | string |
| Query | nextpage_opaque_marker <i>optional</i> | Marker to obtain the next page of a paged response. Shall be supported by the EM/VNF if the EM/VNF supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|---|---------------------------|
| 200 | <p>200 OK Shall be returned when information about zero or more VNF indicators was queried successfully. The response body shall contain in an array the representations of all VNF indicators that match the attribute-based filtering parameters, i.e. zero or more representations of VNF indicators as defined in clause 8.5.2.2. If the "filter" URI parameter was supplied in the request, the data in the response body shall have been transformed according to the rules specified in clause 5.2.2 of ETSI GS NFV-SOL 013. If the EM/VNF supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource, inclusion of the Link HTTP header in this response shall follow the provisions in clause 5.4.2.3 of ETSI GS NFV-SOL 013.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>Version (string) : The used API version.</p> <p>Link (string) : Reference to other resources. Used for paging in the present document, see clause 4.7.2.1.</p> | < Response 200 > array |

| HTTP Code | Description | Schema |
|-----------|---|--------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 400 |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 500 |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 503 |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 504 |

Response 200

| Name | Description | Schema |
|---|---|------------------------|
| _links <i>required</i> | Links for this resource. | _links |
| id <i>required</i> | An identifier that is unique within a VNF descriptor. | string |
| name <i>optional</i> | Human readable name of the indicator. Shall be present if defined in the VNFD. | string |
| value <i>required</i> | Provides the value of the indicator. The value format is defined in the VNFD. ETSI GS NFV-SOL 001 specifies the structure and format of the VNFD based on TOSCA specifications. | object |
| vnfInstanceId <i>required</i> | An identifier with the intention of being globally unique. | string |

_links

| Name | Description | Schema |
|---------------------------------------|--|-----------------------------|
| self <i>required</i> | This type represents a link to a resource using an absolute URI. | self |
| vnfInstance <i>required</i> | This type represents a link to a resource using an absolute URI. | vnfInstance |

self

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

vnfInstance

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

Response 400

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Query multiple indicators related to a VNF instance.

```
GET /indicators/{vnfInstanceId}
```

Description

Get a list of indicators related to a specific VNF instance. Support of attribute based filtering via query parameters.

Parameters

| Type | Name | Description | Schema |
|--------|---|--|--------|
| Header | Authorization <i>optional</i> | The authorization token for the request. Reference: IETF RFC 7235 | string |
| Header | Version <i>required</i> | Version of the API requested to use when responding to this request. | string |
| Path | vnfInstanceId <i>required</i> | Service Unavailable Identifier of the VNF instance to which the VNF indicators applies. NOTE: This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new VNF instance resource. It can also be retrieved from the "id" attribute in the payload body of that response. | string |
| Query | filter <i>optional</i> | Attribute-based filtering expression according to clause 5.2 of ETSI GS NFV-SOL 013. The VNFM shall support receiving this parameter as part of the URI query string. The EM/VNF shall support receiving filtering parameters as part of the URI query string. The VNFM may supply filtering parameters. All attribute names that appear in the VnfIndicator data type and in data types referenced from it shall be supported in attribute-based filtering parameters. EXAMPLE objects obj1: {"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]} obj2: {"id":456, "weight":500, "parts":[{"id":3, "color":"green"}, {"id":4, "color":"blue"}]} Request 1: GET .../container Response 1: [{"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]}, {"id":456, "weight":500, "parts":[{"id":3, "color":"green"}, {"id":4, "color":"blue"}]}] Request 2: GET .../container?filter=(eq.weight,100) Response 2: [{"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]}] | string |

| Type | Name | Description | Schema |
|-------|--|--|--------|
| Query | nextpage_opaque_marker <i>optional</i> | Marker to obtain the next page of a paged response. Shall be supported by the EM/VNF if the EM/VNF supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|--|---|
| 200 | <p>200 OK Shall be returned when information about zero or more VNF indicators was queried successfully. The response body shall contain in an array the representations of all VNF indicators that are related to the particular VNF instance and that match the attribute filter., i.e. zero or more representations of VNF indicators as defined in clause 8.5.2.2. If the "filter" URI parameter was supplied in the request, the data in the response body shall have been transformed according to the rules specified in clause 5.2.2 of ETSI GS NFV-SOL 013. If the EM/VMF supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource, inclusion of the Link HTTP header in this response shall follow the provisions in clause 5.4.2.3 of ETSI GS NFV-SOL 013.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>Version (string) : The used API version.</p> <p>Link (string) : Reference to other resources. Used for paging in the present document, see clause 4.7.2.1.</p> | < Response 200 > array |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 400</p> |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 500 |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 503 |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 504 |

Response 200

| Name | Description | Schema |
|---|---|------------------------|
| _links <i>required</i> | Links for this resource. | _links |
| id <i>required</i> | An identifier that is unique within a VNF descriptor. | string |
| name <i>optional</i> | Human readable name of the indicator. Shall be present if defined in the VNFD. | string |
| value <i>required</i> | Provides the value of the indicator. The value format is defined in the VNFD. ETSI GS NFV-SOL 001 specifies the structure and format of the VNFD based on TOSCA specifications. | object |
| vnfInstanceId <i>required</i> | An identifier with the intention of being globally unique. | string |

_links

| Name | Description | Schema |
|---------------------------------------|--|-----------------------------|
| self <i>required</i> | This type represents a link to a resource using an absolute URI. | self |
| vnfInstance <i>required</i> | This type represents a link to a resource using an absolute URI. | vnfInstance |

self

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

vnfInstance

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

Response 400

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|--------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Read an individual VNF indicator related to a VNF instance.

```
GET /indicators/{vnfInstanceId}/{indicatorId}
```

Description

Read an individual VNF indicator related to a specific VNF instance. NOTE: This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new VNF instance resource. It can also be retrieved from the "id" attribute in the payload body of that response.

Parameters

| Type | Name | Description | Schema |
|--------|---|---|--------|
| Header | Authorization <i>optional</i> | The authorization token for the request. Reference: IETF RFC 7235 | string |
| Header | Version <i>required</i> | Version of the API requested to use when responding to this request. | string |
| Path | indicatorId <i>required</i> | Identifier of the VNF indicator. | string |
| Path | vnfInstanceId <i>required</i> | Service Unavailable Identifier of the VNF instance to which the VNF indicators applies. NOTE: This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new VNF instance resource. It can also be retrieved from the "id" attribute in the payload body of that response. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 200 | 200 OK Shall be returned when the VNF indicator has been read successfully. The response body shall contain the representation of the VNF indicator. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version. | Response 200 |

| HTTP Code | Description | Schema |
|-----------|---|--------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 400 |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 500 |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 503 |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 504 |

Response 200

| Name | Description | Schema |
|---|---|------------------------|
| _links <i>required</i> | Links for this resource. | _links |
| id <i>required</i> | An identifier that is unique within a VNF descriptor. | string |
| name <i>optional</i> | Human readable name of the indicator. Shall be present if defined in the VNFD. | string |
| value <i>required</i> | Provides the value of the indicator. The value format is defined in the VNFD. ETSI GS NFV-SOL 001 specifies the structure and format of the VNFD based on TOSCA specifications. | object |
| vnfInstanceId <i>required</i> | An identifier with the intention of being globally unique. | string |

_links

| Name | Description | Schema |
|---------------------------------------|--|-----------------------------|
| self <i>required</i> | This type represents a link to a resource using an absolute URI. | self |
| vnfInstance <i>required</i> | This type represents a link to a resource using an absolute URI. | vnfInstance |

self

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

vnfInstance

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

Response 400

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Create a new subscription to VNF indicator change notifications

POST /subscriptions

Description

This method creates a new subscription. As the result of successfully executing this method, a new "Individual subscription" resource as defined in clause 8.4.6 shall have been created. This method shall not trigger any notification. Creation of two "Individual subscription" resources with the same callbackURI and the same filter can result in performance degradation and will provide duplicates of notifications to the VNFM, and might make sense only in very rare use cases. Consequently, the API producer may either allow creating a new "Individual subscription" resource if another "Individual subscription" resource with the same filter and callbackUri already exists (in which case it shall return the "201 Created" response code), or may decide to not create a duplicate "Individual subscription" resource (in which case it shall return a "303 See Other" response code referencing the existing "Individual subscription" resource with the same filter and callbackUri). This method shall follow the provisions specified in the tables 8.4.5.3.1-1 and 8.4.5.3.1-2 for URI query parameters, request and response data structures, and response codes

Parameters

| Type | Name | Description | Schema |
|--------|---|--|---|
| Header | Accept <i>required</i> | Content-Types that are acceptable for the response. Reference: IETF RFC 7231 | string |
| Header | Authorization <i>optional</i> | The authorization token for the request. Reference: IETF RFC 7235 | string |
| Header | Content-Type <i>required</i> | The MIME type of the body of the request. Reference: IETF RFC 7231 | string |
| Header | Version <i>required</i> | Version of the API requested to use when responding to this request. | string |
| Body | vnfIndicatorSubscriptionRequest <i>required</i> | Details of the subscription to be created. | vnfIndicatorSubscriptionRequest |

vnfIndicatorSubscriptionRequest

| Name | Description | Schema |
|--|--|--------------------------------|
| authentication <i>optional</i> | | authentication |
| callbackUri <i>required</i> | String formatted according to IETF RFC 3986. | string |

| Name | Description | Schema |
|----------------------------------|--|------------------------|
| filter <i>optional</i> | This type represents a subscription filter related to notifications about VNF indicator value changes. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute). | filter |

authentication

| Name | Description | Schema |
|---|--|---|
| authType <i>required</i> | Defines the types of Authentication / Authorization which the API consumer is willing to accept when receiving a notification. Permitted values: * BASIC: In every HTTP request to the notification endpoint, use HTTP Basic authentication with the client credentials. * OAUTH2_CLIENT_CREDENTIALS: In every HTTP request to the notification endpoint, use an OAuth 2.0 Bearer token, obtained using the client credentials grant type. * TLS_CERT: Every HTTP request to the notification endpoint is sent over a mutually authenticated TLS session, i.e. not only the server is authenticated, but also the client is authenticated during the TLS tunnel setup. | < enum (BASIC, OAUTH2_CLIENT_CREDENTIALS, TLS_CERT) > array |
| paramsBasic <i>optional</i> | Parameters for authentication/authorization using BASIC. Shall be present if authType is "BASIC" and the contained information has not been provisioned out of band. Shall be absent otherwise. | paramsBasic |
| paramsOauth2ClientCredentials <i>optional</i> | Parameters for authentication/authorization using OAUTH2_CLIENT_CREDENTIALS. Shall be present if authType is "OAUTH2_CLIENT_CREDENTIALS" and the contained information has not been provisioned out of band. Shall be absent otherwise. | paramsOauth2ClientCredentials |

paramsBasic

| Name | Description | Schema |
|------------------------------------|--|--------|
| password <i>optional</i> | Password to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band. | string |

| Name | Description | Schema |
|------------------------------------|--|--------|
| userName <i>optional</i> | Username to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band. | string |

paramsOauth2ClientCredentials

| Name | Description | Schema |
|--|---|--------|
| clientId <i>optional</i> | Client identifier to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band. The clientId and clientPassword passed in a subscription shall not be the same as the clientId and clientPassword that are used to obtain authorization for API requests. Client credentials may differ between subscriptions. The value of clientPassword should be generated by a random process. | string |
| clientPassword <i>optional</i> | Client password to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band. The clientId and clientPassword passed in a subscription shall not be the same as the clientId and clientPassword that are used to obtain authorization for API requests. Client credentials may differ between subscriptions. The value of clientPassword should be generated by a random process. | string |
| tokenEndpoint <i>optional</i> | String formatted according to IETF RFC 3986. | string |

filter

| Name | Description | Schema |
|---|---|---|
| indicatorIds <i>optional</i> | Match particular VNF indicator identifiers. | < string > array |
| vnfInstanceSubscriptionFilter <i>optional</i> | This type represents subscription filter criteria to match VNF instances. | vnfInstanceSubscriptionFilter |

vnfInstanceSubscriptionFilter

| Name | Description | Schema |
|--|--|--|
| vnfInstanceIds <i>optional</i> | If present, match VNF instances with an instance identifier listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfInstanceNames <i>optional</i> | If present, match VNF instances with a VNF Instance Name listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfProductsFromProviders <i>optional</i> | If present, match VNF instances that belong to VNF products from certain providers. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < vnfProductsFromProviders > array |
| vnfdIds <i>optional</i> | If present, match VNF instances that were created based on a VNFD identified by one of the vnfdId values listed in this attribute. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |

vnfProductsFromProviders

| Name | Description | Schema |
|---------------------------------------|---|---------------------------------------|
| vnfProducts <i>optional</i> | If present, match VNF instances that belong to VNF products with certain product names, from one particular provider. | < vnfProducts > array |
| vnfProvider <i>required</i> | Name of the VNF provider to match. | string |

vnfProducts

| Name | Description | Schema |
|--|---|------------------------------------|
| versions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain versions and a certain product name, from one particular provider. | < versions > array |
| vnfProductName <i>required</i> | Name of the VNF product to match. | string |

versions

| Name | Description | Schema |
|--|--|------------------|
| vnfSoftwareVersion <i>required</i> | A version. | string |
| vnfdVersions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider. | < string > array |

Responses

| HTTP Code | Description | Schema |
|------------|---|--|
| 201 | <p>201 CREATED Shall be returned when the subscription has been created successfully. The response body shall contain a representation of the created "Individual subscription" resource.</p> <p>Headers :</p> <p>Location (string (URI)) : Pointer to the created subscription resource.</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : The used API version.</p> | < Response 201 > array |

| HTTP Code | Description | Schema |
|-----------|---|------------------------------|
| 303 | <p>303 See Other</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | No Content |
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 400 |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 500 |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 503 |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 504 |

Response 201

| Name | Description | Schema |
|---------------------------------------|--|------------------------|
| _links <i>required</i> | Links for this resource. | _links |
| callbackUri <i>required</i> | The URI of the endpoint to send the notification to. | string (url) |
| filter <i>optional</i> | This type represents a subscription filter related to notifications about VNF indicator value changes. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute). | filter |
| id <i>required</i> | An identifier with the intention of being globally unique. | string |

_links

| Name | Description | Schema |
|--------------------------------|--|----------------------|
| self <i>required</i> | This type represents a link to a resource using an absolute URI. | self |

self

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

filter

| Name | Description | Schema |
|---|---|---|
| indicatorIds <i>optional</i> | Match particular VNF indicator identifiers. | < string > array |
| vnfInstanceSubscriptionFilter <i>optional</i> | This type represents subscription filter criteria to match VNF instances. | vnfInstanceSubscriptionFilter |

vnfInstanceSubscriptionFilter

| Name | Description | Schema |
|--|--|--|
| vnfInstanceIds <i>optional</i> | If present, match VNF instances with an instance identifier listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfInstanceNames <i>optional</i> | If present, match VNF instances with a VNF Instance Name listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfProductsFromProviders <i>optional</i> | If present, match VNF instances that belong to VNF products from certain providers. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < vnfProductsFromProviders > array |
| vnfdIds <i>optional</i> | If present, match VNF instances that were created based on a VNFD identified by one of the vnfdId values listed in this attribute. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |

vnfProductsFromProviders

| Name | Description | Schema |
|---------------------------------------|---|---------------------------------------|
| vnfProducts <i>optional</i> | If present, match VNF instances that belong to VNF products with certain product names, from one particular provider. | < vnfProducts > array |
| vnfProvider <i>required</i> | Name of the VNF provider to match. | string |

vnfProducts

| Name | Description | Schema |
|--|---|------------------------------------|
| versions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain versions and a certain product name, from one particular provider. | < versions > array |
| vnfProductName <i>required</i> | Name of the VNF product to match. | string |

versions

| Name | Description | Schema |
|--|--|------------------|
| vnfSoftwareVersion <i>required</i> | A version. | string |
| vnfdVersions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider. | < string > array |

Response 400

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|--------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|--------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Query multiple subscriptions.

```
GET /subscriptions
```

Description

Service Unavailable The GET method queries the list of active subscriptions of the functional block that invokes the method. It can be used e.g. for resynchronization after error situations.

Parameters

| Type | Name | Description | Schema |
|-------|--|--|--------|
| Query | filter <i>optional</i> | Attribute-based filtering expression according to clause 5.2 of ETSI GS NFV-SOL 013. The EM shall and the VNF may support receiving this parameter as part of the URI query string. The VNFM may supply this parameter. All attribute names that appear in the VnfIndicatorSubscription data type and in data types referenced from it shall be supported in the filter expression. If receiving, this parameter is not supported, a 400 Bad Request response shall be returned (see table 8.4.5.3.2-2). EXAMPLE objects obj1: {"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]} obj2: {"id":456, "weight":500, "parts":[{"id":3, "color":"green"}, {"id":4, "color":"blue"}]} Request 1: GET .../container Response 1: [{"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]}, {"id":456, "weight":500, "parts":[{"id":3, "color":"green"}, {"id":4, "color":"blue"}]}] Request 2: GET .../container?filter=(eq.weight,100) Response 2: [{"id":123, "weight":100, "parts":[{"id":1, "color":"red"}, {"id":2, "color":"green"}]}] | string |
| Query | nextpage_opaque_marker <i>optional</i> | Marker to obtain the next page of a paged response. Shall be supported by the EM if the EM supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|--|---------------------------|
| 200 | <p>200 OK Shall be returned when the list of subscriptions was queried successfully. The response body shall contain in an array the representations of all active subscriptions of the functional block that invokes the method which match the attribute filter, i.e. zero or more representations of VNF indicators subscriptions as defined in clause 8.5.2.4. If the "filter" URI parameter was supplied in the request, the data in the response body shall have been transformed according to the rules specified in clause 5.2.2 of ETSI GS NFV SOL 013. If the EM supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource, inclusion of the Link HTTP header in this response shall follow the provisions in clause 5.4.2.3 of ETSI GS NFV-SOL 013.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>Version (string) : The used API version.</p> <p>Link (string) : Reference to other resources. Used for paging in the present document, see clause 4.7.2.1.</p> | < Response 200 > array |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 400</p> |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 500 |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 503 |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 504 |

Response 200

| Name | Description | Schema |
|---------------------------------------|--|------------------------|
| _links <i>required</i> | Links for this resource. | _links |
| callbackUri <i>required</i> | The URI of the endpoint to send the notification to. | string (url) |
| filter <i>optional</i> | This type represents a subscription filter related to notifications about VNF indicator value changes. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute). | filter |
| id <i>required</i> | An identifier with the intention of being globally unique. | string |

_links

| Name | Description | Schema |
|--------------------------------|--|----------------------|
| self <i>required</i> | This type represents a link to a resource using an absolute URI. | self |

self

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

filter

| Name | Description | Schema |
|---|---|---|
| indicatorIds <i>optional</i> | Match particular VNF indicator identifiers. | < string > array |
| vnfInstanceSubscriptionFilter <i>optional</i> | This type represents subscription filter criteria to match VNF instances. | vnfInstanceSubscriptionFilter |

vnfInstanceSubscriptionFilter

| Name | Description | Schema |
|--|--|--|
| vnfInstanceIds <i>optional</i> | If present, match VNF instances with an instance identifier listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfInstanceNames <i>optional</i> | If present, match VNF instances with a VNF Instance Name listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfProductsFromProviders <i>optional</i> | If present, match VNF instances that belong to VNF products from certain providers. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < vnfProductsFromProviders > array |
| vnfdIds <i>optional</i> | If present, match VNF instances that were created based on a VNFD identified by one of the vnfdId values listed in this attribute. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |

vnfProductsFromProviders

| Name | Description | Schema |
|---------------------------------------|---|---------------------------------------|
| vnfProducts <i>optional</i> | If present, match VNF instances that belong to VNF products with certain product names, from one particular provider. | < vnfProducts > array |
| vnfProvider <i>required</i> | Name of the VNF provider to match. | string |

vnfProducts

| Name | Description | Schema |
|--|---|------------------------------------|
| versions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain versions and a certain product name, from one particular provider. | < versions > array |
| vnfProductName <i>required</i> | Name of the VNF product to match. | string |

versions

| Name | Description | Schema |
|--|--|------------------|
| vnfSoftwareVersion <i>required</i> | A version. | string |
| vnfdVersions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider. | < string > array |

Response 400

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|--------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|--------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Read an individual subscription.

```
GET /subscriptions/{subscriptionId}
```

Description

Service Unavailable This resource represents an individual subscription. The client can use this resource to read and to terminate a subscription to notifications related to VNF indicator value changes.

Parameters

| Type | Name | Description | Schema |
|---------------|---|--|--------|
| Header | Authorization <i>optional</i> | The authorization token for the request. Reference: IETF RFC 7235 | string |
| Header | Version <i>required</i> | Version of the API requested to use when responding to this request. | string |

| Type | Name | Description | Schema |
|------|--|---|--------|
| Path | subscriptionId <i>required</i> | Identifier of this subscription. NOTE: This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new subscription resource. It can also be retrieved from the "id" attribute in the payload body of that response. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 200 | 200 OK Shall be returned when information about an individual subscription has been read successfully. The response body shall contain the representation of the "Individual subscription" resource. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version. | Response 200 |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 400</p> |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 500 |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 503 |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 504 |

Response 200

| Name | Description | Schema |
|---------------------------------------|--|------------------------|
| _links <i>required</i> | Links for this resource. | _links |
| callbackUri <i>required</i> | The URI of the endpoint to send the notification to. | string (url) |
| filter <i>optional</i> | This type represents a subscription filter related to notifications about VNF indicator value changes. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute). | filter |
| id <i>required</i> | An identifier with the intention of being globally unique. | string |

_links

| Name | Description | Schema |
|--------------------------------|--|----------------------|
| self <i>required</i> | This type represents a link to a resource using an absolute URI. | self |

self

| Name | Description | Schema |
|--------------------------------|--|--------|
| href <i>required</i> | String formatted according to IETF RFC 3986. | string |

filter

| Name | Description | Schema |
|---|---|---|
| indicatorIds <i>optional</i> | Match particular VNF indicator identifiers. | < string > array |
| vnfInstanceSubscriptionFilter <i>optional</i> | This type represents subscription filter criteria to match VNF instances. | vnfInstanceSubscriptionFilter |

vnfInstanceSubscriptionFilter

| Name | Description | Schema |
|--|--|--|
| vnfInstanceIds <i>optional</i> | If present, match VNF instances with an instance identifier listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfInstanceNames <i>optional</i> | If present, match VNF instances with a VNF Instance Name listed in this attribute. The attributes "vnfInstanceIds" and "vnfInstanceNames" are alternatives to reference to particular VNF Instances in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |
| vnfProductsFromProviders <i>optional</i> | If present, match VNF instances that belong to VNF products from certain providers. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < vnfProductsFromProviders > array |
| vnfdIds <i>optional</i> | If present, match VNF instances that were created based on a VNFD identified by one of the vnfdId values listed in this attribute. The attributes "vnfdIds" and "vnfProductsFromProviders" are alternatives to reference to VNF instances that are based on certain VNFDs in a filter. They should not be used both in the same filter instance, but one alternative should be chosen. | < string > array |

vnfProductsFromProviders

| Name | Description | Schema |
|---------------------------------------|---|---------------------------------------|
| vnfProducts <i>optional</i> | If present, match VNF instances that belong to VNF products with certain product names, from one particular provider. | < vnfProducts > array |
| vnfProvider <i>required</i> | Name of the VNF provider to match. | string |

vnfProducts

| Name | Description | Schema |
|--|---|------------------------------------|
| versions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain versions and a certain product name, from one particular provider. | < versions > array |
| vnfProductName <i>required</i> | Name of the VNF product to match. | string |

versions

| Name | Description | Schema |
|--|--|------------------|
| vnfSoftwareVersion <i>required</i> | A version. | string |
| vnfdVersions <i>optional</i> | If present, match VNF instances that belong to VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider. | < string > array |

Response 400

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|---------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|----------------------------------|--|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|--------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Delete a subscription

```
DELETE /subscriptions/{subscriptionId}
```

Description

This method terminates an individual subscription. As the result of successfully executing this method, the "Individual subscription" resource shall not exist any longer. This means that no notifications for that subscription shall be sent to the formerly-subscribed API consumer. NOTE: Due to race conditions, some notifications might still be received by the formerly-subscribed API consumer for a certain time period after the deletion.

Parameters

| Type | Name | Description | Schema |
|---------------|---|--|--------|
| Header | Authorization <i>optional</i> | The authorization token for the request. Reference: IETF RFC 7235 | string |

| Type | Name | Description | Schema |
|--------|--|---|--------|
| Header | Version <i>required</i> | Version of the API requested to use when responding to this request. | string |
| Path | subscriptionId <i>required</i> | Service Unavailable Identifier of this subscription. NOTE: This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new subscription resource. It can also be retrieved from the "id" attribute in the payload body of that response. | string |

Responses

| HTTP Code | Description | Schema |
|-----------|--|------------|
| 204 | 204 NO CONTENT Shall be returned when the subscription has been deleted successfully. The response body shall be empty. Headers : <i>Version</i> (string) : The used API version. | No Content |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 400 | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 400</p> |

| HTTP Code | Description | Schema |
|-----------|---|-------------------------------------|
| 401 | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 401</p> |
| 403 | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 403</p> |

| HTTP Code | Description | Schema |
|-----------|--|--------------|
| 404 | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 404 |
| 405 | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 405 |
| 406 | <p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 406 |

| HTTP Code | Description | Schema |
|-----------|--|------------------------------|
| 416 | <p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 416 |
| 422 | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 422 |
| 429 | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | Response 429 |

| HTTP Code | Description | Schema |
|-----------|--|-------------------------------------|
| 500 | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 500</p> |
| 503 | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 503</p> |
| 504 | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> | <p>Response 504</p> |

Response 400

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 401

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 403

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 404

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 405

| Name | Description | Schema |
|----------------------------------|--|--------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 406

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 416

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|---------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 422

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 429

| Name | Description | Schema |
|----------------------------------|--|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name | Description | Schema |
|------------------------------------|---|---------------|
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 500

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |

| Name | Description | Schema |
|---------------------------------|---|---------------|
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 503

| Name | Description | Schema |
|------------------------------------|---|---------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |

| Name | Description | Schema |
|--------------------------------|--|--------------|
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

Response 504

| Name | Description | Schema |
|------------------------------------|---|--------------|
| detail <i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |
| instance <i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |
| status <i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer |
| title <i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string |
| type <i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |