

SOL003 - VNF Package Management interface

Overview

SOL003 - VNF Package Management interface IMPORTANT: Please note that this file might be not aligned to the current version of the ETSI Group Specification it refers to. In case of discrepancies the published ETSI Group Specification takes precedence. Please report bugs to <https://forge.etsi.org/rep/nfv/SOL002-SOL003/issues>

Version information

Version : 2.1.0-impl:etsi.org:ETSI_NFV_OpenAPI:1

License information

License : ETSI Forge copyright notice

License URL : <https://forge.etsi.org/etsi-forge-copyright-notice.txt>

Terms of service : null

URI scheme

BasePath : /vnfpgm/v2

Schemes : HTTPS

Consumes

- `application/json`

Produces

- `application/json`

External Docs

Description : ETSI GS NFV-SOL 003 V2.8.1

URL : https://www.etsi.org/deliver/etsi_gs/NFV-SOL/001_099/003/02.08.01_60/gs_NFV-SOL003v020801p.pdf

Paths

POST /api_versions

Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /api_versions

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
200	200 OK API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version.	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
413	<p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 413
414	<p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 414
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 422
429	<p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 429

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
apiVersions <i>required</i>	Version(s) supported for the API signaled by the uriPrefix attribute.	< apiVersions > array
uriPrefix <i>required</i>	Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/.	string

apiVersions

Name	Description	Schema
isDeprecated <i>optional</i>	If such information is available, this attribute indicates whether use of the version signaled by the version attribute is deprecated (true) or not (false). A deprecated version is still supported by the API producer but is recommended not to be used any longer. When a version is no longer supported, it does not appear in the response body.	boolean
retirementDate <i>optional</i>	Date-time stamp. Representation: String formatted according to IETF RFC 3339.	string (date-time)
version <i>required</i>	Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 9.1 (SOL013).	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 413

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 414

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 429

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

PUT /api_versions

Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

DELETE /api_versions

Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

PATCH /api_versions

Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /onboarded_vnf_packages

Description

Query VNF Package Info. The GET method queries the information of the VNF packages matching the filter. This method shall follow the provisions specified in the tables 10.4.2.3.2-1 and 10.4.2.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Query	all_fields <i>optional</i>	Include all complex attributes in the response. See clause 5.3 of ETSI GS NFV SOL 013 for details. The VNFM shall support this parameter.	string
Query	exclude_default <i>optional</i>	Indicates to exclude the following complex attributes from the response. See clause 5.3 of ETSI GS NFV SOL 013 for details. The VNFM shall support this parameter. The following attributes shall be excluded from the VnfPkgInfo structure in the response body if this parameter is provided, or none of the parameters "all_fields," "fields", "exclude_fields", "exclude_default" are provided: - softwareImages - additionalArtifacts - userDefinedData.	string

Type	Name	Description	Schema
Query	exclude_fields <i>optional</i>	Complex attributes to be excluded from the response. See clause 5.3 of ETSI GS NFV SOL 013 for details. The VNFM should support this parameter. The following attributes shall be excluded from the VnfPkgInfo structure in the response body if this parameter is provided, or none of the parameters "all_fields," "fields", "exclude_fields", "exclude_default" are provided: - softwareImages - additionalArtifacts - userDefinedData. - checksum - onboardingFailureDetails	string
Query	fields <i>optional</i>	Complex attributes to be included into the response. See clause 5.3 of ETSI GS NFV SOL 013 for details. The VNFM should support this parameter.	string
Query	filter <i>optional</i>	Attribute-based filtering expression according to clause 5.2 of ETSI GS NFV SOL 013. The VNFM shall support receiving this parameter as part of the URI query string. The NFVO may supply this parameter. All attribute names that appear in the VnfPkgInfo and in data types referenced from it shall be supported by the VNFM in the filter expression.	string
Query	nextpage_opaque_marker <i>optional</i>	Marker to obtain the next page of a paged response. Shall be supported by the NFVO if the NFVO supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when information about zero or more VNF packages has been queried successfully. The response body shall contain in an array the VNF package info representations that match the attribute filter, i.e. zero or more VNF package info representations as defined in clause 10.5.2.2. If the "filter" URI parameter or one of the "all_fields", "fields" (if supported), "exclude_fields" (if supported) or "exclude_default" URI parameters was supplied in the request, the data in the response body shall have been transformed according to the rules specified in clauses 5.2.2 and 5.3.2 of ETSI GS NFV-SOL 013, respectively. If the VNFM supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource, inclusion of the Link HTTP header in this response shall follow the provisions in clause 5.4.2.3 of ETSI GS NFV-SOL 013.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> <p>Link (string) : Reference to other resources. Used for paging in the present document, see clause 4.7.2.1.</p>	< Response 200 > array

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 503</p>

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
_links <i>required</i>	Links to resources related to this resource.	_links
additionalArtifacts <i>optional</i>	Information about VNF package artifacts contained in the VNF package that are not software images. Every local and external artifact declared in the manifest shall be included, except the software images and the files that make up the parts of the VNFD (see clause 10.4.4.3.2). Signature files and certificate files are not considered as artifacts, however, the content of the "Licenses" and "Testing" directories in the VNF package is. This attribute shall not be present before the VNF package content is on-boarded. Otherwise, this attribute shall be present if the VNF package contains additional artifacts.	< additionalArtifacts > array
checksum <i>optional</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
compatibleSpecifications <i>optional</i>	Indicates which versions of the ETSI GS NFV-SOL 004 specification the package complies to, as defined in the manifest of the package. Each entry shall be formatted as defined in clause 4.3.2 of ETSI GS NFV-SOL 004.	< string > array
id <i>required</i>	An identifier with the intention of being globally unique.	string

Name	Description	Schema
onboardingFailureDetails <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [19] is reproduced in this structure. Compared to the general framework defined in IETF RFC 7807 [19], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [19] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error. The description column only provides some explanation of the meaning to Facilitate understanding of the design. For a full description, see IETF RFC 7807 [19].</p>	onboardingFailureDetails
onboardingState <i>optional</i>	<p>CREATED: The "Individual VNF package" resource has been created. UPLOADING: The associated VNF package content is being uploaded. PROCESSING: The associated VNF package content is being processed, e.g., validation. ONBOARDED: The associated VNF package content has been on-boarded successfully. ERROR: There was an error during upload of the VNF package content or external artifacts, or during VNF package processing.</p>	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED, ERROR)
operationalState <i>required</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)
packageSecurityOption <i>required</i>	<p>Signals the security option used by the package as defined in clause 5.1 of ETSI GS NFV-SOL 004. Valid values: OPTION_1, OPTION_2</p>	enum (OPTION_1, OPTION_2)
signingCertificate <i>optional</i>	<p>A string defined in IETF RFC 8259.</p>	string

Name	Description	Schema
softwareImages <i>optional</i>	Information about VNF package artifacts that are software images. This attribute shall not be present before the VNF package content is on-boarded. Otherwise, this attribute shall be present unless it has been requested to be excluded per attribute selector.	< softwareImages > array
usageState <i>required</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
userDefinedData <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
vnfProductName <i>optional</i>	A string defined in IETF RFC 8259.	string
vnfProvider <i>optional</i>	A string defined in IETF RFC 8259.	string
vnfSoftwareVersion <i>optional</i>	A version.	string
vnfdId <i>optional</i>	An identifier with the intention of being globally unique.	string
vnfdVersion <i>optional</i>	A version.	string

links

Name	Description	Schema
packageContent <i>required</i>	This type represents a link to a resource using an absolute URI.	packageContent

Name	Description	Schema
self <i>required</i>	This type represents a link to a resource using an absolute URI.	self
vnfd <i>optional</i>	This type represents a link to a resource using an absolute URI.	vnfd

packageContent

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

self

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

vnfd

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

additionalArtifacts

Name	Description	Schema
artifactClassification <i>optional</i>	Marks specific types of artifacts as defined in the VNF package. If none of the specific classes listed below applies, the attribute shall not be present. Valid values: - HISTORY: a history artifact as per clause 4.3.3 in ETSI GS NFV-SOL 004 - TESTING: a testing artifact as per clause 4.3.4 in ETSI GS NFV-SOL 004 - LICENSE: a license artifact as per clause 4.3.5 in ETSI GS NFV-SOL 004	enum (HISTORY, TESTING, LICENSE)
artifactPath <i>required</i>	A string defined in IETF RFC 8259.	string
artifactURI <i>optional</i>	String formatted according to IETF RFC 3986.	string

Name	Description	Schema
checksum <i>required</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
isEncrypted <i>required</i>	The Boolean is a data type having two values (true and false).	boolean
metadata <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
nonManoArtif actSetId <i>optional</i>	A string defined in IETF RFC 8259.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

onboardingFailureDetails

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

softwareImages

Name	Description	Schema
checksum <i>required</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
containerFormat <i>required</i>	Container format indicates whether the software image is in a file format that also contains metadata about the actual software. Permitted values: - AKI: a kernel image format - AMI: a machine image format - ARI: a ramdisk image format - BARE: the image does not have a container or metadata envelope - DOCKER: docker container format - OVA: OVF package in a tarfile - OVF: OVF container format The list of permitted values was taken from "Container formats" in http://docs.openstack.org/image-guide/image-formats.html	enum (AKI, AMI, ARI, BARE, DOCKER, OVA, OVF)

Name	Description	Schema
createdAt <i>required</i>	Date-time stamp. Representation: String formatted according to IETF RFC 3339.	string (date-time)
diskFormat <i>required</i>	Disk format of a software image is the format of the underlying disk image. Permitted values: - AKI: a kernel image format - AMI: a machine image format - ARI: a ramdisk image format - ISO: an archive format for the data contents of an optical disc, such as CD-ROM - QCOW2: a common disk image format, which can expand dynamically and supports copy on write - RAW: an unstructured disk image format - VDI: a common disk image format - VHD: a common disk image format - VHDX: enhanced version of VHD format - VMDK: a common disk image format The list of permitted values was adapted from "Disk formats" in http://docs.openstack.org/image-guide/image-formats.html	enum (AKI, AMI, ISO, QCOW2, RAW, VDI, VHD, VHDX, VMDK)
id <i>required</i>	An identifier that is unique within a VNF descriptor.	string
imagePath <i>required</i>	A string defined in IETF RFC 8259.	string
imageUri <i>optional</i>	String formatted according to IETF RFC 3986.	string
isEncrypted <i>required</i>	The Boolean is a data type having two values (true and false).	boolean
minDisk <i>required</i>	The minimal disk for this software image in bytes.	integer
minRam <i>required</i>	The minimal RAM for this software image in bytes.	integer
name <i>required</i>	A string defined in IETF RFC 8259.	string
provider <i>required</i>	A string defined in IETF RFC 8259.	string
size <i>required</i>	Size of this software image in bytes.	integer

Name	Description	Schema
userMetadata <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
version <i>required</i>	A version.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /onboarded_vnf_packages/{vnfdId}

Description

Query VNF Package Info. The GET method reads the information of an individual VNF package. This method shall follow the provisions specified in the tables 10.4.3.3.2-1 and 10.4.3.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfdId <i>required</i>	Identifier of the VNFD and the VNF package. The identifier is allocated by the VNF provider. This identifier can be retrieved from the "vnfdId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when information of the VNF package has been read successfully. The response body shall contain the VNF package info representation defined in clause 10.5.2.2.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
_links <i>required</i>	Links to resources related to this resource.	_links
additionalArtifacts <i>optional</i>	Information about VNF package artifacts contained in the VNF package that are not software images. Every local and external artifact declared in the manifest shall be included, except the software images and the files that make up the parts of the VNFD (see clause 10.4.4.3.2). Signature files and certificate files are not considered as artifacts, however, the content of the "Licenses" and "Testing" directories in the VNF package is. This attribute shall not be present before the VNF package content is on-boarded. Otherwise, this attribute shall be present if the VNF package contains additional artifacts.	< additionalArtifacts > array
checksum <i>optional</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
compatibleSpecifications <i>optional</i>	Indicates which versions of the ETSI GS NFV-SOL 004 specification the package complies to, as defined in the manifest of the package. Each entry shall be formatted as defined in clause 4.3.2 of ETSI GS NFV-SOL 004.	< string > array
id <i>required</i>	An identifier with the intention of being globally unique.	string

Name	Description	Schema
onboardingFailureDetails <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [19] is reproduced in this structure. Compared to the general framework defined in IETF RFC 7807 [19], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [19] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error. The description column only provides some explanation of the meaning to Facilitate understanding of the design. For a full description, see IETF RFC 7807 [19].</p>	onboardingFailureDetails
onboardingState <i>optional</i>	<p>CREATED: The "Individual VNF package" resource has been created. UPLOADING: The associated VNF package content is being uploaded. PROCESSING: The associated VNF package content is being processed, e.g., validation. ONBOARDED: The associated VNF package content has been on-boarded successfully. ERROR: There was an error during upload of the VNF package content or external artifacts, or during VNF package processing.</p>	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED, ERROR)
operationalState <i>required</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)
packageSecurityOption <i>required</i>	<p>Signals the security option used by the package as defined in clause 5.1 of ETSI GS NFV-SOL 004. Valid values: OPTION_1, OPTION_2</p>	enum (OPTION_1, OPTION_2)
signingCertificate <i>optional</i>	<p>A string defined in IETF RFC 8259.</p>	string

Name	Description	Schema
softwareImages <i>optional</i>	Information about VNF package artifacts that are software images. This attribute shall not be present before the VNF package content is on-boarded. Otherwise, this attribute shall be present unless it has been requested to be excluded per attribute selector.	< softwareImages > array
usageState <i>required</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
userDefinedData <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
vnfProductName <i>optional</i>	A string defined in IETF RFC 8259.	string
vnfProvider <i>optional</i>	A string defined in IETF RFC 8259.	string
vnfSoftwareVersion <i>optional</i>	A version.	string
vnfdId <i>optional</i>	An identifier with the intention of being globally unique.	string
vnfdVersion <i>optional</i>	A version.	string

links

Name	Description	Schema
packageContent <i>required</i>	This type represents a link to a resource using an absolute URI.	packageContent

Name	Description	Schema
self <i>required</i>	This type represents a link to a resource using an absolute URI.	self
vnfd <i>optional</i>	This type represents a link to a resource using an absolute URI.	vnfd

packageContent

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

self

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

vnfd

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

additionalArtifacts

Name	Description	Schema
artifactClassification <i>optional</i>	Marks specific types of artifacts as defined in the VNF package. If none of the specific classes listed below applies, the attribute shall not be present. Valid values: - HISTORY: a history artifact as per clause 4.3.3 in ETSI GS NFV-SOL 004 - TESTING: a testing artifact as per clause 4.3.4 in ETSI GS NFV-SOL 004 - LICENSE: a license artifact as per clause 4.3.5 in ETSI GS NFV-SOL 004	enum (HISTORY, TESTING, LICENSE)
artifactPath <i>required</i>	A string defined in IETF RFC 8259.	string
artifactURI <i>optional</i>	String formatted according to IETF RFC 3986.	string

Name	Description	Schema
checksum <i>required</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
isEncrypted <i>required</i>	The Boolean is a data type having two values (true and false).	boolean
metadata <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
nonManoArtif actSetId <i>optional</i>	A string defined in IETF RFC 8259.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

onboardingFailureDetails

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

softwareImages

Name	Description	Schema
checksum <i>required</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
containerFormat <i>required</i>	Container format indicates whether the software image is in a file format that also contains metadata about the actual software. Permitted values: - AKI: a kernel image format - AMI: a machine image format - ARI: a ramdisk image format - BARE: the image does not have a container or metadata envelope - DOCKER: docker container format - OVA: OVF package in a tarfile - OVF: OVF container format The list of permitted values was taken from "Container formats" in http://docs.openstack.org/image-guide/image-formats.html	enum (AKI, AMI, ARI, BARE, DOCKER, OVA, OVF)

Name	Description	Schema
createdAt <i>required</i>	Date-time stamp. Representation: String formatted according to IETF RFC 3339.	string (date-time)
diskFormat <i>required</i>	Disk format of a software image is the format of the underlying disk image. Permitted values: - AKI: a kernel image format - AMI: a machine image format - ARI: a ramdisk image format - ISO: an archive format for the data contents of an optical disc, such as CD-ROM - QCOW2: a common disk image format, which can expand dynamically and supports copy on write - RAW: an unstructured disk image format - VDI: a common disk image format - VHD: a common disk image format - VHDX: enhanced version of VHD format - VMDK: a common disk image format The list of permitted values was adapted from "Disk formats" in http://docs.openstack.org/image-guide/image-formats.html	enum (AKI, AMI, ISO, QCOW2, RAW, VDI, VHD, VHDX, VMDK)
id <i>required</i>	An identifier that is unique within a VNF descriptor.	string
imagePath <i>required</i>	A string defined in IETF RFC 8259.	string
imageUri <i>optional</i>	String formatted according to IETF RFC 3986.	string
isEncrypted <i>required</i>	The Boolean is a data type having two values (true and false).	boolean
minDisk <i>required</i>	The minimal disk for this software image in bytes.	integer
minRam <i>required</i>	The minimal RAM for this software image in bytes.	integer
name <i>required</i>	A string defined in IETF RFC 8259.	string
provider <i>required</i>	A string defined in IETF RFC 8259.	string
size <i>required</i>	Size of this software image in bytes.	integer

Name	Description	Schema
userMetadata <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
version <i>required</i>	A version.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /onboarded_vnf_packages/{vnfdId}/artifacts

Description

The GET method shall return an archive that contains a set of artifacts according to the provisions for inclusion/exclusion defined below, embedded in a directory structure being the same as in the VNF package. The criteria for exclusion/inclusion of an artifact in the archive are defined as follows: - Artifacts that are software images shall be excluded from the archive. - Artifacts that are not software images and that are external to the VNF package shall be excluded from the archive unless the URI query parameter "include_external_artifacts" has been provided. External artifacts shall be included in the archive using the content of the "artifactPath" attribute as the path. - All additional artifacts included in the VNF package that are MANO artifacts shall be included in the archive, unless the URI query parameter "exclude_all_mano_artifacts" has been provided, in which case such artifacts shall be excluded. - All additional artifacts included in the VNF package that are non-MANO artifacts shall be included in the archive, unless: - The URI query parameter "exclude_all_non_mano_artifacts" has been provided, in which case such artifacts shall be excluded; - The URI query parameter "select_non_mano_artifact_sets" has been provided and is supported by the NFVO, in which case only those non-MANO artifacts shall be included whose non-MANO artifact set identifier matches one of the values of the query parameter. Package metadata such as manifest file or VNFD shall not be included in the archive. This method shall follow the provisions specified in the tables 10.4.5a.3.2-1 and 10.4.5a.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. The "Accept" HTTP header shall be set to "application/zip".	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string

Type	Name	Description	Schema
Header	Range <i>optional</i>	The request may contain a "Range" HTTP header to obtain single range of bytes from the VNF package file. This can be used to continue an aborted transmission. If the NFVO does not support range requests, it should return the whole file with a 200 OK response instead.	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfdId <i>required</i>	Identifier of the VNFD and the VNF package. The identifier is allocated by the VNF provider. This identifier can be retrieved from the "vnfdId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	exclude_all_mano_artifacts <i>optional</i>	Flag (i.e. parameter without value) that instructs the NFVO to exclude the set of additional MANO artifacts (i.e. those that are not images) from the response payload body. The NFVO shall support this parameter. The VNFM may supply this parameter.	string
Query	exclude_all_non_mano_artifacts <i>optional</i>	Flag (i.e. parameter without value) that instructs the NFVO to exclude the set of non-MANO artifacts from the response payload body. The NFVO shall support this parameter. The VNFM may supply this parameter.	string
Query	include_external_artifacts <i>optional</i>	Flag (i.e. parameter without value) that instructs the NFVO to include external artifacts in the response payload body. It shall not be treated as an error if this flag is provided but there is no external artifact to include in the result. If this parameter is missing, no external artifacts shall be included. The NFVO shall support this parameter. The VNFM may supply this parameter.	string

Type	Name	Description	Schema
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall include in the ZIP archive the individual signatures and, if provided, related certificates for the included artifacts, in the format in which they are provided in the VNF package. If this parameter is not given, the NFVO shall only provide copies of the artifact files. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string
Query	select_non_mano_artifacts <i>optional</i>	Comma-separated list of non-MANO artifact set identifiers for which the artifacts are to be included in the response body. The NFVO should support this parameter. If the NFVO does not support this parameter, it shall ignore it, i.e. provide a response as if no parameter was provided. The VNFM may supply this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the whole content of the archive containing the artifact files has been read successfully. The payload body shall be a ZIP archive containing the requested set of artifacts selected according to the provisions specified above in this clause, and, if the flag "include_signatures" was provided in the related request, the applicable signature files and, if available, the separate certificate files from the VNF package. The "Content-Type" HTTP header shall be set to "application/zip".</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response. The "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the content type cannot be determined, the header shall be set to the value "application/octet-stream".</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
206	<p>206 PARTIAL CONTENT If the NFVO supports range requests, this response shall be returned when a single consecutive byte range from the content of the archive that would have been returned in a "200 OK" response has been read successfully according to the request. The response body shall contain the requested part of the archive. The "Content-Type" HTTP header shall be set to "application/zip". The "Content-Range" HTTP header shall be provided according to IETF RFC 7233.</p> <p>Headers :</p> <p>Content-Range (string)</p> <p>Content-Type (string) : The MIME type of the body of the response. The "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the content type cannot be determined, the header shall be set to the value "application/octet-stream".</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET

/onboarded_vnf_packages/{vnfdId}/artifacts/{artifactPath}

Description

Fetch VNF Package Artifacts. The GET method fetches the content of an artifact within a VNF package. This method shall follow the provisions specified in the tables 10.4.6.3.2-1 and 10.4.6.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response.	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Range <i>optional</i>	The request may contain a "Range" HTTP header to obtain single range of bytes from the VNF package file. This can be used to continue an aborted transmission. If the "Range" header is present in the request and the NFVO does not support responding to range requests with a 206 response, it shall return a 200 OK response instead as defined below.	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string

Type	Name	Description	Schema
Path	artifactPath <i>required</i>	For an artifact contained as a file in the VNF package, this variable shall contain a sequence of one or more path segments representing the path of the artifact within the VNF package, relative to the root of the package. EXAMPLE: foo/bar/m%40ster.sh For an external artifact represented as a URI in the VNF package manifest, this variable shall contain a sequence of one or more path segments as synthesized by the NFVO (see clause 10.5.3.3), representing this artifact. See notes 2 and 4. NOTE 2: This identifier can be retrieved from the "artifactPath" attribute of the applicable "additionalArtifacts" entry in the body of the response to a GET request querying the "Individual VNF package" or the "VNF packages" resource. NOTE 4: Since multiple path segments are allowed to be contained in this variable, the "/" character that separates these segments is not percent-encoded. Each individual segment is percent-encoded if necessary as defined in clause 4.1 of ETSI GS NFV-SOL 013.	string
Path	vnfdId <i>required</i>	Identifier of the VNFD and the VNF package. The identifier is allocated by the VNF provider. This identifier can be retrieved from the "vnfdId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall return the artifact and related security information (such as signature and optional certificate) in a ZIP archive. If this parameter is not given, the NFVO shall provide only a copy of the artifact file. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the whole content of the artifact file has been read successfully. If the "include_signatures" request URI parameter was not provided in the related request, the payload body shall contain a copy of the artifact file from the VNF package, as defined by ETSI GS NFV-SOL 004 and the "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the artifact is encrypted, the header shall be set to the value "application/cms" (IETF RFC 7193). If the content type cannot be determined, the header shall be set to the value "application/octet-stream". If the "include_signatures" request URI parameter was provided in the related request, the "Content-Type" HTTP header shall be set to "application/zip and the payload body shall contain a ZIP archive which includes: • a copy of the artifact file from the VNF package, as defined by ETSI GS NFV SOL 004; • the related security information (individual signature file and optional related individual certificate file).</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response. The "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the content type cannot be determined, the header shall be set to the value "application/octet-stream".</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
206	<p>206 PARTIAL CONTENT If the NFVO supports range requests and the "include_signatures" request URI parameter was not present in the related request, this response shall be returned when a single consecutive byte range from the content of the artifact file, if the NFVO supports range requests has been read successfully according to the request. The response body shall contain the requested part of the VNF package file. The "Content-Range" HTTP header shall be provided according to IETF RFC 7233. The "Content-Type" HTTP header shall be set as defined above for the "200 OK" response.</p> <p>Headers :</p> <p>Content-Range (string)</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /onboarded_vnf_packages/{vnfdId}/manifest

Description

Query VNF Package Manifest The GET method reads the content of the manifest within a VNF package. This method shall follow the provisions specified in the tables 10.4.4a.3.2-1 and 10.4.4a.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Permitted values: "text/plain" and/or "application/zip" Reference: IETF RFC 7231	enum (text/plain, application/zip, text/plain+application/zip)
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfdId <i>required</i>	Identifier of the VNFD and the VNF package. The identifier is allocated by the VNF provider. This identifier can be retrieved from the "vnfdId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall return the manifest and related security information (such as certificate) in a ZIP archive. If this parameter is not given, the NFVO shall provide only a copy of the manifest file. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the content of the manifest has been read successfully. If the "include_signatures" URI query parameter was absent in the request, or if the manifest file has all security-related information embedded (i.e. there is no separate certificate file), the payload body shall contain a copy of the manifest file of the VNF package and the "Content-Type" HTTP header shall be set to "text/plain". If the "include_signatures" URI query parameter was present in the related request and the manifest file does not have all the security-related information embedded (i.e. there is a separate certificate file), the "Content-Type" HTTP header shall be set to "application/zip" and the payload body shall contain a ZIP archive which includes:</p> <ul style="list-style-type: none"> • a copy of the manifest file of the VNF package; • a copy of the related individual certificate file. <p>Headers :</p> <p>Content-Type (enum (text/plain, application/zip)) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET

/onboarded_vnf_packages/{vnfdId}/package_content

Description

Fetch VNF Package. The GET method fetches the content of a VNF package identified by the VNF

package identifier allocated by the NFVO. The content of the package is provided as onboarded, i.e. depending on the security option used, the CSAR or the CSAR wrapped in a ZIP archive together with an external signature is returned, as defined in clause 5.1 of ETSI GS NFV-SOL 004. NOTE: Information about the applicable security option can be obtained by evaluating the "packageSecurityOption" attribute in the "VnfPkgInfo" structure. This method shall follow the provisions specified in the tables 10.4.5.3.2-1 and 10.4.5.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response.	enum (text/plain, application/zip)
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Range <i>optional</i>	The request may contain a "Range" HTTP header to obtain single range of bytes from the VNF package file. This can be used to continue an aborted transmission. If the "Range" header is present in the request and the NFVO does not support responding to range requests with a 206 response, it shall return a 200 OK response instead as defined below.	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfdId <i>required</i>	Identifier of the VNFD and the VNF package. The identifier is allocated by the VNF provider. This identifier can be retrieved from the "vnfdId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the whole content of the VNF package file has been read successfully. The response body shall include a copy of the VNF package file. The "Content-Type HTTP" header shall be set according to the type of the file, i.e. to "application/zip" for a VNF Package as defined in ETSI GS NFV SOL 004.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content
206	<p>206 PARTIAL CONTENT If the NFVO supports range requests, this response shall be returned when a single consecutive byte range from the content of the VNF package file has been read successfully according to the request. The response body shall contain the requested part of the VNF package file. The "Content-Range" HTTP header shall be provided according to IETF RFC 7233. The "Content-Type" HTTP header shall be set as defined above for the "200 OK" response.</p> <p>Headers :</p> <p>Content-Range (string)</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /onboarded_vnf_packages/{vnfdId}/vnfd

Description

Query VNF Package Info The GET method reads the content of the VNFD within a VNF package. The VNFD is implemented as a collection of one or more files. A ZIP archive embedding these files shall be returned when reading this resource. The default format of the ZIP archive shall comply with

CSAR format as specified in ETSI GS NFV-SOL 004 where only the files representing the VNFD and information needed to navigate the ZIP archive and to identify the file that is the entry point for parsing the VNFD, and, if requested, further security information are included, and software images as well as other artifacts referenced from the YAML files are excluded. This means that the structure of the ZIP archive shall correspond to the directory structure used in the VNF package and that the archive shall contain the following files from the package: • TOSCA.meta (if available in the package). • The main TOSCA definitions YAML file (either as referenced from TOSCA.meta or available as a file with the extension ".yaml" or ".yml" from the root of the archive). • Every component of the VNFD referenced (recursively) from the main TOSCA definitions YAML file.

NOTE 1: For a VNFD based on TOSCA, it includes all the imported type definition files as indicated in the top level service template and in any of the lower level service template if it has any as described in ETSI GS NFV-SOL 001. NOTE 2: For a VNFD based on YANG, it includes the file as indicated by the "yang_definitions" keyname in the metadata section of the main yaml file as described in ETSI GS NFV-SOL 004. • The related security information, if the "include_signatures" URI parameter is provided, as follows: - the manifest file - the singleton certificate file in the root of the VNF package (if available in the package) - the signing certificates of the individual files included in the ZIP archive (if available in the package) - the signatures of the individual files (if available in the package)

Three examples are provided below. NOTE 3: These examples do not show the security related files. EXAMPLE 1: Assuming a request is sent for the following VNF package (as described in clause A.1 in ETSI GS NFV-SOL 004): !—TOSCA-Metadata !— TOSCA.meta (metadata for navigating the ZIP file) !—Definitions !— MRF.yaml (main VNFD file) !— OtherTemplates (e.g. type definitions, referenced by the main VNFD file) !—Files !— ChangeLog.txt !— image(s) !— other artifacts !—Tests !— file(s) !—Licenses !— file(s) !—Scripts !— install.sh !— MRF.mf

The NFVO will return a ZIP file of the following format:
!-----TOSCA-Metadata
!----- TOSCA.meta
!-----Definitions
!----- MRF.yaml
!----- OtherTemplates

EXAMPLE 2: Assuming a request is sent for the following VNF package (a VNF package without a TOSCA-Metadata directory, as described in clause A.2 in ETSI GS NFV-SOL 004): !—MRF.yaml (main VNFD file) !—MRF.mf !—ChangeLog.txt !—Tests !— file(s) !—Licenses !— file(s) !—Artifacts !— install.sh !— start.yang

The NFVO will return a ZIP file of the following format:
!-----MRF.yaml

EXAMPLE 3: Assuming a request is sent for the following VNF package (a VNF package with the YANG VNFD without a TOSCA-Metadata directory, as described in clause A.3 in ETSI GS NFV SOL 004): !—CompanyVNFD.yaml !—CompanyVNFD.xml !—CompanyVNFD.mf !—ChangeLog.txt !—Files !—Instance Data Files !— start.xml !—Licenses !—Scripts !— install.sh

The NFVO will return a ZIP file of the following format:
 !----CompanyVNFD.yaml
 !----CompanyVNFD.xml (indicated in the yang_definitions metadata in
 CompanyVNFD.yaml)

This method shall follow the provisions specified in the tables 10.4.4.3.2-1 and 10.4.4.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Permitted values: "text/plain" and/or "application/zip" Reference: IETF RFC 7231	enum (text/plain, application/zip, text/plain+application/zip)
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfdId <i>required</i>	Identifier of the VNFD and the VNF package. The identifier is allocated by the VNF provider. This identifier can be retrieved from the "vnfdId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall include in the ZIP archive the security information as specified above. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the content of the VNFD has been read successfully. The payload body shall contain a copy of the file representing the VNFD or a ZIP file that contains the file or multiple files representing the VNFD, as specified above. The "Content-Type" HTTP header shall be set according to the format of the returned file, i.e. to "text/plain" for a YAML file or to "application/zip" for a ZIP file.</p> <p>Headers :</p> <p>Content-Type (enum (text/plain, application/zip)) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 409

HTTP Code	Description	Schema
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 503</p>

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

POST /subscriptions

Description

Subscribe. The POST method creates a new subscription. This method shall follow the provisions specified in the tables 10.4.7.3.1-1 and 10.4.7.3.1-2 for URI query parameters, request and response data structures, and response codes. As the result of successfully executing this method, a new "Individual subscription" resource as defined in clause 10.4.8 shall have been created. This method shall not trigger any notification. Creation of two "Individual subscription" resources with the same callback URI and the same filter can result in performance degradation and will provide duplicates of notifications to the VNFM, and might make sense only in very rare use cases. Consequently, the NFVO may either allow creating a new "Individual subscription" resource if another "Individual subscription" resource with the same filter and callback URI already exists (in which case it shall return the "201 Created" response code), or may decide to not create a duplicate "Individual subscription" resource (in which case it shall return a "303 See Other" response code referencing the existing "Individual subscription" resource with the same filter and callback URI).

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Content-Type <i>required</i>	The MIME type of the body of the request. Reference: IETF RFC 7231	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Body	PkgmSubscriptionRequest <i>required</i>	Representation of the created subscription resource. The HTTP response shall include a "Location" HTTP header that points to the created subscription resource.	PkgmSubscriptionRequest

PkgmSubscriptionRequest

Name	Description	Schema
authentication <i>optional</i>		authentication
callbackUri <i>required</i>	String formatted according to IETF RFC 3986.	string
filter <i>optional</i>	This type represents a subscription filter related to notifications related to VNF package management. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	filter

authentication

Name	Description	Schema
authType <i>required</i>	Defines the types of Authentication / Authorization which the API consumer is willing to accept when receiving a notification. Permitted values: * BASIC: In every HTTP request to the notification endpoint, use HTTP Basic authentication with the client credentials. * OAUTH2_CLIENT_CREDENTIALS: In every HTTP request to the notification endpoint, use an OAuth 2.0 Bearer token, obtained using the client credentials grant type. * TLS_CERT: Every HTTP request to the notification endpoint is sent over a mutually authenticated TLS session, i.e. not only the server is authenticated, but also the client is authenticated during the TLS tunnel setup.	< enum (BASIC, OAUTH2_CLIENT_CREDENTIALS, TLS_CERT) > array
paramsBasic <i>optional</i>	Parameters for authentication/authorization using BASIC. Shall be present if authType is "BASIC" and the contained information has not been provisioned out of band. Shall be absent otherwise.	paramsBasic
paramsOAuth2ClientCredentials <i>optional</i>	Parameters for authentication/authorization using OAUTH2_CLIENT_CREDENTIALS. Shall be present if authType is "OAUTH2_CLIENT_CREDENTIALS" and the contained information has not been provisioned out of band. Shall be absent otherwise.	paramsOAuth2ClientCredentials

paramsBasic

Name	Description	Schema
password <i>optional</i>	Password to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string
userName <i>optional</i>	Username to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string

paramsOAuth2ClientCredentials

Name	Description	Schema
clientId <i>optional</i>	Client identifier to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band. The clientId and clientPassword passed in a subscription shall not be the same as the clientId and clientPassword that are used to obtain authorization for API requests. Client credentials may differ between subscriptions. The value of clientPassword should be generated by a random process.	string
clientPassword <i>optional</i>	Client password to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band. The clientId and clientPassword passed in a subscription shall not be the same as the clientId and clientPassword that are used to obtain authorization for API requests. Client credentials may differ between subscriptions. The value of clientPassword should be generated by a random process.	string
tokenEndpoint <i>optional</i>	String formatted according to IETF RFC 3986.	string

filter

Name	Description	Schema
notificationTypes <i>optional</i>	Match particular notification types. Permitted values: - VnfPackageOnboardingNotification - VnfPackageChangeNotification The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.	< enum (VnfPackageOnboardingNotification, VnfPackageChangeNotification) > array
operationalState <i>optional</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)

Name	Description	Schema
usageState <i>optional</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. - NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
vnfPkgId <i>optional</i>	Match VNF packages with a package identifier listed in the attribute. May be present if the "notificationTypes" attribute contains the value "VnfPackageChangeNotification", and shall be absent otherwise. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfProductsFromProviders <i>optional</i>	If present, match VNF packages that contain VNF products from certain providers. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< vnfProductsFromProviders > array
vnfdId <i>optional</i>	Match VNF packages with a VNFD identifier listed in the attribute. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfmInfo <i>optional</i>	Match strings that specify VNFMs compatible with the VNF. See table 10.5.2.2-1.	< string > array

vnfProductsFromProviders

Name	Description	Schema
vnfProducts <i>optional</i>	If present, match VNF packages that contain VNF products with certain product names, from one particular provider.	< vnfProducts > array
vnfProvider <i>required</i>	A string defined in IETF RFC 8259.	string

vnfProducts

Name	Description	Schema
versions <i>optional</i>	If present, match VNF packages that contain VNF products with certain versions and a certain product name, from one particular provider.	< versions > array
vnfProductName <i>required</i>	A string defined in IETF RFC 8259.	string

versions

Name	Description	Schema
vnfSoftwareVersion <i>required</i>	A version.	string
vnfdVersions <i>optional</i>	If present, match VNF packages that contain VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider.	< string > array

Responses

HTTP Code	Description	Schema
201	<p>201 CREATED Shall be returned when the subscription has been created successfully. The response body shall contain a representation of the created "Individual subscription" resource. The HTTP response shall include a "Location" HTTP header that points to the created resource.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>Location (string (url)) : The resource URI of the created VNF instance.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	< Response 201 > array

HTTP Code	Description	Schema
303	<p>303 See Other</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 400

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 503</p>

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 201

Name	Description	Schema
_links <i>required</i>	Links to resources related to this resource.	_links
callbackUri <i>required</i>	String formatted according to IETF RFC 3986.	string
filter <i>optional</i>	This type represents a subscription filter related to notifications related to VNF package management. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	filter
id <i>required</i>	An identifier with the intention of being globally unique.	string

_links

Name	Description	Schema
self <i>required</i>	This type represents a link to a resource using an absolute URI.	self

self

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

filter

Name	Description	Schema
notificationTypes <i>optional</i>	Match particular notification types. Permitted values: - VnfPackageOnboardingNotification - VnfPackageChangeNotification The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.	< enum (VnfPackageOnboardingNotification, VnfPackageChangeNotification) > array
operationalState <i>optional</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)
usageState <i>optional</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
vnfPkgId <i>optional</i>	Match VNF packages with a package identifier listed in the attribute. May be present if the "notificationTypes" attribute contains the value "VnfPackageChangeNotification", and shall be absent otherwise. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfProductsFromProviders <i>optional</i>	If present, match VNF packages that contain VNF products from certain providers. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< vnfProductsFromProviders > array

Name	Description	Schema
vnfdId <i>optional</i>	Match VNF packages with a VNFD identifier listed in the attribute. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfmInfo <i>optional</i>	Match strings that specify VNFMs compatible with the VNF. See table 10.5.2.2-1.	< string > array

vnfProductsFromProviders

Name	Description	Schema
vnfProducts <i>optional</i>	If present, match VNF packages that contain VNF products with certain product names, from one particular provider.	< vnfProducts > array
vnfProvider <i>required</i>	A string defined in IETF RFC 8259.	string

vnfProducts

Name	Description	Schema
versions <i>optional</i>	If present, match VNF packages that contain VNF products with certain versions and a certain product name, from one particular provider.	< versions > array
vnfProductName <i>required</i>	A string defined in IETF RFC 8259.	string

versions

Name	Description	Schema
vnfSoftwareVersion <i>required</i>	A version.	string
vnfdVersions <i>optional</i>	If present, match VNF packages that contain VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider.	< string > array

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /subscriptions

Description

Query Subscription Information. The GET method queries the list of active subscriptions of the functional block that invokes the method. It can be used e.g. for resynchronization after error situations. This method shall follow the provisions specified in the tables 10.4.7.3.2-1 and 10.4.7.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string

Type	Name	Description	Schema
Query	filter <i>optional</i>	Attribute-based filtering expression according to clause 5.2 of ETSI GS NFV SOL 013. The VNFM shall support receiving this parameter as part of the URI query string. The NFVO may supply this parameter. All attribute names that appear in the PkgmSubscription and in data types referenced from it shall be supported by the VNFM in the filter expression.	string
Query	nextpage_opaque_marker <i>optional</i>	Marker to obtain the next page of a paged response. Shall be supported by the NFVO if the NFVO supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the list of subscriptions has been queried successfully. The response body shall contain in an array the representations of all active subscriptions of the functional block that invokes the method, i.e. zero or more representations of VNF package management subscriptions as defined in clause 10.5.2.4. If the "filter" URI parameter was supplied in the request, the data in the response body shall have been transformed according to the rules specified in clause 5.2.2 of ETSI GS NFV-SOL 013 If the VNFM supports alternative 2 (paging) according to clause 5.4.2.1 of ETSI GS NFV-SOL 013 for this resource, inclusion of the Link HTTP header in this response shall follow the provisions in clause 5.4.2.3 of ETSI GS NFV-SOL 013.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p> <p>Link (string) : Reference to other resources. Used for paging in the present document, see clause 4.7.2.1.</p>	< Response 200 > array

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 503</p>

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
_links <i>required</i>	Links to resources related to this resource.	_links
callbackUri <i>required</i>	String formatted according to IETF RFC 3986.	string
filter <i>optional</i>	This type represents a subscription filter related to notifications related to VNF package management. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	filter
id <i>required</i>	An identifier with the intention of being globally unique.	string

_links

Name	Description	Schema
self <i>required</i>	This type represents a link to a resource using an absolute URI.	self

self

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

filter

Name	Description	Schema
notificationTypes <i>optional</i>	Match particular notification types. Permitted values: - VnfPackageOnboardingNotification - VnfPackageChangeNotification The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.	< enum (VnfPackageOnboardingNotification, VnfPackageChangeNotification) > array
operationalState <i>optional</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)
usageState <i>optional</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
vnfPkgId <i>optional</i>	Match VNF packages with a package identifier listed in the attribute. May be present if the "notificationTypes" attribute contains the value "VnfPackageChangeNotification", and shall be absent otherwise. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfProductsFromProviders <i>optional</i>	If present, match VNF packages that contain VNF products from certain providers. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< vnfProductsFromProviders > array

Name	Description	Schema
vnfdId <i>optional</i>	Match VNF packages with a VNFD identifier listed in the attribute. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfmInfo <i>optional</i>	Match strings that specify VNFMs compatible with the VNF. See table 10.5.2.2-1.	< string > array

vnfProductsFromProviders

Name	Description	Schema
vnfProducts <i>optional</i>	If present, match VNF packages that contain VNF products with certain product names, from one particular provider.	< vnfProducts > array
vnfProvider <i>required</i>	A string defined in IETF RFC 8259.	string

vnfProducts

Name	Description	Schema
versions <i>optional</i>	If present, match VNF packages that contain VNF products with certain versions and a certain product name, from one particular provider.	< versions > array
vnfProductName <i>required</i>	A string defined in IETF RFC 8259.	string

versions

Name	Description	Schema
vnfSoftwareVersion <i>required</i>	A version.	string
vnfdVersions <i>optional</i>	If present, match VNF packages that contain VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider.	< string > array

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /subscriptions/{subscriptionId}

Description

Query Subscription Information. The GET method reads an individual subscription. This method shall follow the provisions specified in the tables 10.4.8.3.2-1 and 10.4.8.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	subscriptionId <i>required</i>	Identifier of this subscription. This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new "Individual subscription" resource. It can also be retrieved from the "id" attribute in the payload body of that response.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when information about an individual subscription has been read successfully. The response body shall contain a representation of the "Individual subscription" resource.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 503</p>

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
_links <i>required</i>	Links to resources related to this resource.	_links
callbackUri <i>required</i>	String formatted according to IETF RFC 3986.	string
filter <i>optional</i>	This type represents a subscription filter related to notifications related to VNF package management. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	filter
id <i>required</i>	An identifier with the intention of being globally unique.	string

_links

Name	Description	Schema
self <i>required</i>	This type represents a link to a resource using an absolute URI.	self

self

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

filter

Name	Description	Schema
notificationTypes <i>optional</i>	Match particular notification types. Permitted values: - VnfPackageOnboardingNotification - VnfPackageChangeNotification The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.	< enum (VnfPackageOnboardingNotification, VnfPackageChangeNotification) > array
operationalState <i>optional</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)
usageState <i>optional</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
vnfPkgId <i>optional</i>	Match VNF packages with a package identifier listed in the attribute. May be present if the "notificationTypes" attribute contains the value "VnfPackageChangeNotification", and shall be absent otherwise. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfProductsFromProviders <i>optional</i>	If present, match VNF packages that contain VNF products from certain providers. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< vnfProductsFromProviders > array

Name	Description	Schema
vnfdId <i>optional</i>	Match VNF packages with a VNFD identifier listed in the attribute. The attributes "vnfProductsFromProviders", "vnfdId" and "vnfPkgId" are alternatives to reference to particular VNF packages in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
vnfmInfo <i>optional</i>	Match strings that specify VNFMs compatible with the VNF. See table 10.5.2.2-1.	< string > array

vnfProductsFromProviders

Name	Description	Schema
vnfProducts <i>optional</i>	If present, match VNF packages that contain VNF products with certain product names, from one particular provider.	< vnfProducts > array
vnfProvider <i>required</i>	A string defined in IETF RFC 8259.	string

vnfProducts

Name	Description	Schema
versions <i>optional</i>	If present, match VNF packages that contain VNF products with certain versions and a certain product name, from one particular provider.	< versions > array
vnfProductName <i>required</i>	A string defined in IETF RFC 8259.	string

versions

Name	Description	Schema
vnfSoftwareVersion <i>required</i>	A version.	string
vnfdVersions <i>optional</i>	If present, match VNF packages that contain VNF products with certain VNFD versions, a certain software version and a certain product name, from one particular provider.	< string > array

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

DELETE /subscriptions/{subscriptionId}

Description

Terminate subscription. The DELETE method terminates an individual subscription. This method shall follow the provisions specified in the tables 10.4.8.3.5-1 and 10.4.8.3.5-2 for URI query parameters, request and response data structures, and response codes. As the result of successfully executing this method, the "Individual subscription" resource shall not exist any longer. This means that no notifications for that subscription shall be sent to the formerly-subscribed API consumer. NOTE: Due to race conditions, some notifications might still be received by the formerly-subscribed API consumer for a certain time period after the deletion.

Parameters

Type	Name	Description	Schema
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string

Type	Name	Description	Schema
Path	subscriptionId <i>required</i>	Identifier of this subscription. This identifier can be retrieved from the resource referenced by the "Location" HTTP header in the response to a POST request creating a new "Individual subscription" resource. It can also be retrieved from the "id" attribute in the payload body of that response.	string

Responses

HTTP Code	Description	Schema
204	<p>204 NO CONTENT Shall be returned when the "Individual subscription" resource has been deleted successfully.</p> <p>Headers :</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 422
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /vnf_packages/{vnfPkgId}

Description

Query VNF Package Info. The GET method reads the information of an individual VNF package. This method shall follow the provisions specified in the tables 10.4.3.3.2-1 and 10.4.3.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string

Type	Name	Description	Schema
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfPkgId <i>required</i>	Identifier of the VNF package. The identifier is allocated by the NFVO. This identifier can be retrieved from the "vnfPkgId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signature <i>optional</i>	If this parameter is provided, the NFVO shall include in the ZIP archive the security information as specified above. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when information of the VNF package has been read successfully. The response body shall contain the VNF package info representation defined in clause 10.5.2.2.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
_links <i>required</i>	Links to resources related to this resource.	_links
additionalArtifacts <i>optional</i>	Information about VNF package artifacts contained in the VNF package that are not software images. Every local and external artifact declared in the manifest shall be included, except the software images and the files that make up the parts of the VNFD (see clause 10.4.4.3.2). Signature files and certificate files are not considered as artifacts, however, the content of the "Licenses" and "Testing" directories in the VNF package is. This attribute shall not be present before the VNF package content is on-boarded. Otherwise, this attribute shall be present if the VNF package contains additional artifacts.	< additionalArtifacts > array
checksum <i>optional</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
compatibleSpecifications <i>optional</i>	Indicates which versions of the ETSI GS NFV-SOL 004 specification the package complies to, as defined in the manifest of the package. Each entry shall be formatted as defined in clause 4.3.2 of ETSI GS NFV-SOL 004.	< string > array
id <i>required</i>	An identifier with the intention of being globally unique.	string
onboardingFailureDetails <i>optional</i>	The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [19] is reproduced in this structure. Compared to the general framework defined in IETF RFC 7807 [19], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [19] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error. The description column only provides some explanation of the meaning to Facilitate understanding of the design. For a full description, see IETF RFC 7807 [19].	onboardingFailureDetails

Name	Description	Schema
onboardingState <i>optional</i>	CREATED: The "Individual VNF package" resource has been created. UPLOADING: The associated VNF package content is being uploaded. PROCESSING: The associated VNF package content is being processed, e.g., validation. ONBOARDED: The associated VNF package content has been on-boarded successfully. ERROR: There was an error during upload of the VNF package content or external artifacts, or during VNF package processing.	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED, ERROR)
operationalState <i>required</i>	<ul style="list-style-type: none"> ENABLED: The VNF package is enabled, i.e. it can be used for the creation of new "Individual VNF instance" resources. DISABLED: The VNF package is disabled, i.e. it shall not be used for the creation of further "Individual VNF instance" resources (unless and until the VNF package is re-enabled). 	enum (ENABLED, DISABLED)
packageSecurityOption <i>required</i>	Signals the security option used by the package as defined in clause 5.1 of ETSI GS NFV-SOL 004. Valid values: OPTION_1, OPTION_2	enum (OPTION_1, OPTION_2)
signingCertificate <i>optional</i>	A string defined in IETF RFC 8259.	string
softwareImages <i>optional</i>	Information about VNF package artifacts that are software images. This attribute shall not be present before the VNF package content is on-boarded. Otherwise, this attribute shall be present unless it has been requested to be excluded per attribute selector.	< softwareImages > array
usageState <i>required</i>	<ul style="list-style-type: none"> IN_USE: "Individual VNF instance" resources created from this VNF package exist. NOT_IN_USE: No "Individual VNF instance" resource created from this VNF package exists. 	enum (IN_USE, NOT_IN_USE)
userDefinedData <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object

Name	Description	Schema
vnfProductName <i>optional</i>	A string defined in IETF RFC 8259.	string
vnfProvider <i>optional</i>	A string defined in IETF RFC 8259.	string
vnfSoftwareVersion <i>optional</i>	A version.	string
vnfdId <i>optional</i>	An identifier with the intention of being globally unique.	string
vnfdVersion <i>optional</i>	A version.	string

links

Name	Description	Schema
packageContent <i>required</i>	This type represents a link to a resource using an absolute URI.	packageContent
self <i>required</i>	This type represents a link to a resource using an absolute URI.	self
vnfd <i>optional</i>	This type represents a link to a resource using an absolute URI.	vnfd

packageContent

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

self

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

vnfd

Name	Description	Schema
href <i>required</i>	String formatted according to IETF RFC 3986.	string

additionalArtifacts

Name	Description	Schema
artifactClassification <i>optional</i>	Marks specific types of artifacts as defined in the VNF package. If none of the specific classes listed below applies, the attribute shall not be present. Valid values: - HISTORY: a history artifact as per clause 4.3.3 in ETSI GS NFV-SOL 004 - TESTING: a testing artifact as per clause 4.3.4 in ETSI GS NFV-SOL 004 - LICENSE: a license artifact as per clause 4.3.5 in ETSI GS NFV-SOL 004	enum (HISTORY, TESTING, LICENSE)
artifactPath <i>required</i>	A string defined in IETF RFC 8259.	string
artifactURI <i>optional</i>	String formatted according to IETF RFC 3986.	string
checksum <i>required</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
isEncrypted <i>required</i>	The Boolean is a data type having two values (true and false).	boolean
metadata <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
nonManoArtifactSetId <i>optional</i>	A string defined in IETF RFC 8259.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string
hash <i>required</i>	A string defined in IETF RFC 8259.	string

onboardingFailureDetails

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

softwareImages

Name	Description	Schema
checksum <i>required</i>	This type represents the checksum of a VNF package or an artifact file.	checksum
containerFormat <i>required</i>	Container format indicates whether the software image is in a file format that also contains metadata about the actual software. Permitted values: - AKI: a kernel image format - AMI: a machine image format - ARI: a ramdisk image format - BARE: the image does not have a container or metadata envelope - DOCKER: docker container format - OVA: OVF package in a tarfile - OVF: OVF container format The list of permitted values was taken from "Container formats" in http://docs.openstack.org/image-guide/image-formats.html	enum (AKI, AMI, ARI, BARE, DOCKER, OVA, OVF)
createdAt <i>required</i>	Date-time stamp. Representation: String formatted according to IETF RFC 3339.	string (date-time)
diskFormat <i>required</i>	Disk format of a software image is the format of the underlying disk image. Permitted values: - AKI: a kernel image format - AMI: a machine image format - ARI: a ramdisk image format - ISO: an archive format for the data contents of an optical disc, such as CD-ROM - QCOW2: a common disk image format, which can expand dynamically and supports copy on write - RAW: an unstructured disk image format - VDI: a common disk image format - VHD: a common disk image format - VHDX: enhanced version of VHD format - VMDK: a common disk image format The list of permitted values was adapted from "Disk formats" in http://docs.openstack.org/image-guide/image-formats.html	enum (AKI, AMI, ISO, QCOW2, RAW, VDI, VHD, VHDX, VMDK)
id <i>required</i>	An identifier that is unique within a VNF descriptor.	string

Name	Description	Schema
imagePath <i>required</i>	A string defined in IETF RFC 8259.	string
imageUri <i>optional</i>	String formatted according to IETF RFC 3986.	string
isEncrypted <i>required</i>	The Boolean is a data type having two values (true and false).	boolean
minDisk <i>required</i>	The minimal disk for this software image in bytes.	integer
minRam <i>required</i>	The minimal RAM for this software image in bytes.	integer
name <i>required</i>	A string defined in IETF RFC 8259.	string
provider <i>required</i>	A string defined in IETF RFC 8259.	string
size <i>required</i>	Size of this software image in bytes.	integer
userMetadata <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 8259. In the following example, a list of key-value pairs with four keys ("aString", "aNumber", "anArray" and "anObject") is provided to illustrate that the values associated with different keys can be of different type.	object
version <i>required</i>	A version.	string

checksum

Name	Description	Schema
algorithm <i>required</i>	A string defined in IETF RFC 8259.	string

Name	Description	Schema
hash <i>required</i>	A string defined in IETF RFC 8259.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)

Name	Description	Schema
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /vnf_packages/{vnfPkgId}/artifacts

Description

The GET method shall return an archive that contains a set of artifacts according to the provisions for inclusion/exclusion defined below, embedded in a directory structure being the same as in the VNF package. The criteria for exclusion/inclusion of an artifact in the archive are defined as follows: - Artifacts that are software images shall be excluded from the archive. - Artifacts that are not software images and that are external to the VNF package shall be excluded from the archive unless the URI query parameter "include_external_artifacts" has been provided. External artifacts shall be included in the archive using the content of the "artifactPath" attribute as the path. - All additional artifacts included in the VNF package that are MANO artifacts shall be included in the archive, unless the URI query parameter "exclude_all_mano_artifacts" has been provided, in which case such artifacts shall be excluded. - All additional artifacts included in the VNF package that are non-MANO artifacts shall be included in the archive, unless: - The URI query parameter "exclude_all_non_mano_artifacts" has been provided, in which case such artifacts shall be excluded; - The URI query parameter "select_non_mano_artifact_sets" has been provided and is supported by the NFVO, in which case only those non-MANO artifacts shall be included whose non-MANO artifact set identifier matches one of the values of the query parameter. Package metadata such as manifest file or VNFD shall not be included in the archive. This method shall follow the

provisions specified in the tables 10.4.5a.3.2-1 and 10.4.5a.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. The "Accept" HTTP header shall be set to "application/zip".	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Range <i>optional</i>	The request may contain a "Range" HTTP header to obtain single range of bytes from the VNF package file. This can be used to continue an aborted transmission. If the NFVO does not support range requests, it should return the whole file with a 200 OK response instead.	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfPkgId <i>required</i>	Identifier of the VNF package. The identifier is allocated by the NFVO. This identifier can be retrieved from the "vnfPkgId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification	string
Query	exclude_all_mano_artifacts <i>optional</i>	Flag (i.e. parameter without value) that instructs the NFVO to exclude the set of additional MANO artifacts (i.e. those that are not images) from the response payload body. The NFVO shall support this parameter. The VNFM may supply this parameter.	string
Query	exclude_all_non_mano_artifacts <i>optional</i>	Flag (i.e. parameter without value) that instructs the NFVO to exclude the set of non-MANO artifacts from the response payload body. The NFVO shall support this parameter. The VNFM may supply this parameter.	string

Type	Name	Description	Schema
Query	include_external_artifacts <i>optional</i>	Flag (i.e. parameter without value) that instructs the NFVO to include external artifacts in the response payload body. It shall not be treated as an error if this flag is provided but there is no external artifact to include in the result. If this parameter is missing, no external artifacts shall be included. The NFVO shall support this parameter. The VNFM may supply this parameter.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall include in the ZIP archive the individual signatures and, if provided, related certificates for the included artifacts, in the format in which they are provided in the VNF package. If this parameter is not given, the NFVO shall only provide copies of the artifact files. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string
Query	select_non_mano_artifact_sets <i>optional</i>	Comma-separated list of non-MANO artifact set identifiers for which the artifacts are to be included in the response body. The NFVO should support this parameter. If the NFVO does not support this parameter, it shall ignore it, i.e. provide a response as if no parameter was provided. The VNFM may supply this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the whole content of the archive containing the artifact files has been read successfully. The payload body shall be a ZIP archive containing the requested set of artifacts selected according to the provisions specified above in this clause, and, if the flag "include_signatures" was provided in the related request, the applicable signature files and, if available, the separate certificate files from the VNF package. The "Content-Type" HTTP header shall be set to "application/zip".</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response. The "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the content type cannot be determined, the header shall be set to the value "application/octet-stream".</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content
206	<p>206 PARTIAL CONTENT If the NFVO supports range requests, this response shall be returned when a single consecutive byte range from the content of the archive that would have been returned in a "200 OK" response has been read successfully according to the request. The response body shall contain the requested part of the archive. The "Content-Type" HTTP header shall be set to "application/zip". The "Content-Range" HTTP header shall be provided according to IETF RFC 7233.</p> <p>Headers :</p> <p>Content-Range (string)</p> <p>Content-Type (string) : The MIME type of the body of the response. The "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the content type cannot be determined, the header shall be set to the value "application/octet-stream".</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 409
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /vnf_packages/{vnfPkgId}/artifacts/{artifactPath}

Description

Fetch VNF Package Artifacts. The GET method fetches the content of an artifact within a VNF package. This method shall follow the provisions specified in the tables 10.4.6.3.2-1 and 10.4.6.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response.	string
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Range <i>optional</i>	The request may contain a "Range" HTTP header to obtain single range of bytes from the VNF package file. This can be used to continue an aborted transmission. If the "Range" header is present in the request and the NFVO does not support responding to range requests with a 206 response, it shall return a 200 OK response instead as defined below.	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	artifactPath <i>required</i>	For an artifact contained as a file in the VNF package, this variable shall contain a sequence of one or more path segments representing the path of the artifact within the VNF package, relative to the root of the package. EXAMPLE: foo/bar/m%40ster.sh For an external artifact represented as a URI in the VNF package manifest, this variable shall contain a sequence of one or more path segments as synthesized by the NFVO (see clause 10.5.3.3), representing this artifact. See notes 2 and 4. NOTE 2: This identifier can be retrieved from the "artifactPath" attribute of the applicable "additionalArtifacts" entry in the body of the response to a GET request querying the "Individual VNF package" or the "VNF packages" resource. NOTE 4: Since multiple path segments are allowed to be contained in this variable, the "/" character that separates these segments is not percent-encoded. Each individual segment is percent-encoded if necessary as defined in clause 4.1 of ETSI GS NFV-SOL 013.	string

Type	Name	Description	Schema
Path	vnfPkgId <i>required</i>	Identifier of the VNF package. The identifier is allocated by the NFVO. This identifier can be retrieved from the "vnfPkgId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall return the artifact and related security information (such as signature and optional certificate) in a ZIP archive. If this parameter is not given, the NFVO shall provide only a copy of the artifact file. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the whole content of the artifact file has been read successfully. If the "include_signatures" request URI parameter was not provided in the related request, the payload body shall contain a copy of the artifact file from the VNF package, as defined by ETSI GS NFV-SOL 004 and the "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the artifact is encrypted, the header shall be set to the value "application/cms" (IETF RFC 7193). If the content type cannot be determined, the header shall be set to the value "application/octet-stream". If the "include_signatures" request URI parameter was provided in the related request, the "Content-Type" HTTP header shall be set to "application/zip and the payload body shall contain a ZIP archive which includes: • a copy of the artifact file from the VNF package, as defined by ETSI GS NFV SOL 004; • the related security information (individual signature file and optional related individual certificate file).</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response. The "Content-Type" HTTP header shall be set according to the content type of the artifact file. If the content type cannot be determined, the header shall be set to the value "application/octet-stream".</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
206	<p>206 PARTIAL CONTENT If the NFVO supports range requests and the "include_signatures" request URI parameter was not present in the related request, this response shall be returned when a single consecutive byte range from the content of the artifact file, if the NFVO supports range requests has been read successfully according to the request. The response body shall contain the requested part of the VNF package file. The "Content-Range" HTTP header shall be provided according to IETF RFC 7233. The "Content-Type" HTTP header shall be set as defined above for the "200 OK" response.</p> <p>Headers :</p> <p>Content-Range (string)</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /vnf_packages/{vnfPkgId}/manifest

Description

Query VNF Package Manifest The GET method reads the content of the manifest within a VNF package. This method shall follow the provisions specified in the tables 10.4.4a.3.2-1 and 10.4.4a.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Permitted values: "text/plain" and/or "application/zip" Reference: IETF RFC 7231	enum (text/plain, application/zip, text/plain+application/zip)
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfPkgId <i>required</i>	Identifier of the on-boarded VNF package. The identifier is allocated by the NFVO. This identifier can be retrieved from the "vnfPkgId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall return the manifest and related security information (such as certificate) in a ZIP archive. If this parameter is not given, the NFVO shall provide only a copy of the manifest file. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the content of the manifest has been read successfully. If the "include_signatures" URI query parameter was absent in the request, or if the manifest file has all security-related information embedded (i.e. there is no separate certificate file), the payload body shall contain a copy of the manifest file of the VNF package and the "Content-Type" HTTP header shall be set to "text/plain". If the "include_signatures" URI query parameter was present in the related request and the manifest file does not have all the security-related information embedded (i.e. there is a separate certificate file), the "Content-Type" HTTP header shall be set to "application/zip" and the payload body shall contain a ZIP archive which includes:</p> <ul style="list-style-type: none"> • a copy of the manifest file of the VNF package; • a copy of the related individual certificate file. <p>Headers :</p> <p>Content-Type (enum (text/plain, application/zip)) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /vnf_packages/{vnfPkgId}/package_content

Description

Fetch VNF Package. The GET method fetches the content of a VNF package identified by the VNF package identifier allocated by the NFVO. The content of the package is provided as onboarded, i.e. depending on the security option used, the CSAR or the CSAR wrapped in a ZIP archive together

with an external signature is returned, as defined in clause 5.1 of ETSI GS NFV-SOL 004. NOTE: Information about the applicable security option can be obtained by evaluating the "packageSecurityOption" attribute in the "VnfPkgInfo" structure. This method shall follow the provisions specified in the tables 10.4.5.3.2-1 and 10.4.5.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response.	enum (text/plain, application/zip)
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Range <i>optional</i>	The request may contain a "Range" HTTP header to obtain single range of bytes from the VNF package file. This can be used to continue an aborted transmission. If the "Range" header is present in the request and the NFVO does not support responding to range requests with a 206 response, it shall return a 200 OK response instead as defined below.	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfPkgId <i>required</i>	Identifier of the VNF package. The identifier is allocated by the NFVO. This identifier can be retrieved from the "vnfPkgId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the whole content of the VNF package file has been read successfully. The response body shall include a copy of the VNF package file. The "Content-Type HTTP" header shall be set according to the type of the file, i.e. to "application/zip" for a VNF Package as defined in ETSI GS NFV SOL 004.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content
206	<p>206 PARTIAL CONTENT If the NFVO supports range requests, this response shall be returned when a single consecutive byte range from the content of the VNF package file has been read successfully according to the request. The response body shall contain the requested part of the VNF package file. The "Content-Range" HTTP header shall be provided according to IETF RFC 7233. The "Content-Type" HTTP header shall be set as defined above for the "200 OK" response.</p> <p>Headers :</p> <p>Content-Range (string)</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" HTTP header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
409	<p>409 CONFLICT</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 409</p>
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>

HTTP Code	Description	Schema
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

GET /vnf_packages/{vnfPkgId}/vnfd

Description

Query VNF Package Info The GET method reads the content of the VNFD within a VNF package. The VNFD is implemented as a collection of one or more files. A ZIP archive embedding these files shall be returned when reading this resource. The default format of the ZIP archive shall comply with

CSAR format as specified in ETSI GS NFV-SOL 004 where only the files representing the VNFD and information needed to navigate the ZIP archive and to identify the file that is the entry point for parsing the VNFD, and, if requested, further security information are included, and software images as well as other artifacts referenced from the YAML files are excluded. This means that the structure of the ZIP archive shall correspond to the directory structure used in the VNF package and that the archive shall contain the following files from the package: • TOSCA.meta (if available in the package). • The main TOSCA definitions YAML file (either as referenced from TOSCA.meta or available as a file with the extension ".yaml" or ".yml" from the root of the archive). • Every component of the VNFD referenced (recursively) from the main TOSCA definitions YAML file.

NOTE 1: For a VNFD based on TOSCA, it includes all the imported type definition files as indicated in the top level service template and in any of the lower level service template if it has any as described in ETSI GS NFV-SOL 001. NOTE 2: For a VNFD based on YANG, it includes the file as indicated by the "yang_definitions" keyname in the metadata section of the main yaml file as described in ETSI GS NFV-SOL 004. • The related security information, if the "include_signatures" URI parameter is provided, as follows: - the manifest file - the singleton certificate file in the root of the VNF package (if available in the package) - the signing certificates of the individual files included in the ZIP archive (if available in the package) - the signatures of the individual files (if available in the package)

Three examples are provided below. NOTE 3: These examples do not show the security related files. EXAMPLE 1: Assuming a request is sent for the following VNF package (as described in clause A.1 in ETSI GS NFV-SOL 004): !—TOSCA-Metadata !— TOSCA.meta (metadata for navigating the ZIP file) !—Definitions !— MRF.yaml (main VNFD file) !— OtherTemplates (e.g. type definitions, referenced by the main VNFD file) !—Files !— ChangeLog.txt !— image(s) !— other artifacts !—Tests !— file(s) !—Licenses !— file(s) !—Scripts !— install.sh !— MRF.mf

```
The NFVO will return a ZIP file of the following format:  
!-----TOSCA-Metadata  
    !----- TOSCA.meta  
!-----Definitions  
    !----- MRF.yaml  
    !----- OtherTemplates
```

EXAMPLE 2: Assuming a request is sent for the following VNF package (a VNF package without a TOSCA-Metadata directory, as described in clause A.2 in ETSI GS NFV-SOL 004): !—MRF.yaml (main VNFD file) !—MRF.mf !—ChangeLog.txt !—Tests !— file(s) !—Licenses !— file(s) !—Artifacts !— install.sh !— start.yang

```
The NFVO will return a ZIP file of the following format:  
!-----MRF.yaml
```

EXAMPLE 3: Assuming a request is sent for the following VNF package (a VNF package with the YANG VNFD without a TOSCA-Metadata directory, as described in clause A.3 in ETSI GS NFV SOL 004): !—CompanyVNFD.yaml !—CompanyVNFD.xml !—CompanyVNFD.mf !—ChangeLog.txt !—Files !—Instance Data Files !— start.xml !—Licenses !—Scripts !— install.sh

The NFVO will return a ZIP file of the following format:
 !----CompanyVNFD.yaml
 !----CompanyVNFD.xml (indicated in the yang_definitions metadata in
 CompanyVNFD.yaml)

This method shall follow the provisions specified in the tables 10.4.4.3.2-1 and 10.4.4.3.2-2 for URI query parameters, request and response data structures, and response codes.

Parameters

Type	Name	Description	Schema
Header	Accept <i>required</i>	Content-Types that are acceptable for the response. Permitted values: "text/plain" and/or "application/zip" Reference: IETF RFC 7231	enum (text/plain, application/zip, text/plain+application/zip)
Header	Authorization <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	Version <i>required</i>	Version of the API requested to use when responding to this request.	string
Path	vnfPkgId <i>required</i>	Identifier of the on-boarded VNF package. The identifier is allocated by the NFVO. This identifier can be retrieved from the "vnfPkgId" attribute in the VnfPackageOnboardingNotification or VnfPackageChangeNotification.	string
Query	include_signatures <i>optional</i>	If this parameter is provided, the NFVO shall include in the ZIP archive the security information as specified above. This URI query parameter is a flag, i.e. it shall have no value. The NFVO shall support this parameter.	string

Responses

HTTP Code	Description	Schema
200	<p>200 OK Shall be returned when the content of the VNFD has been read successfully. The payload body shall contain a copy of the file representing the VNFD or a ZIP file that contains the file or multiple files representing the VNFD, as specified above. The "Content-Type" HTTP header shall be set according to the format of the returned file, i.e. to "text/plain" for a YAML file or to "application/zip" for a ZIP file.</p> <p>Headers :</p> <p>Content-Type (enum (text/plain, application/zip)) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 405
409	<p>409 CONFLICT</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 409

HTTP Code	Description	Schema
416	<p>416 Range Not Satisfiable</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 416</p>
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 500</p>
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 503</p>

HTTP Code	Description	Schema
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 409

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)