

# SOL005 - NS Performance Management Notification interface

# Overview

SOL005 - NS Performance Management Notification interface IMPORTANT: Please note that this file might be not aligned to the current version of the ETSI Group Specification it refers to. In case of discrepancies the published ETSI Group Specification takes precedence. Please report bugs to <https://forge.etsi.org/bugzilla/buglist.cgi?component=Nfv-Openapis>

## Version information

*Version* : 1.1.0-impl:etsi.org:ETSI\_NFV\_OpenAPI:1

## License information

*License* : ETSI Forge copyright notice

*License URL* : <https://forge.etsi.org/etsi-forge-copyright-notice.txt>

*Terms of service* : null

## URI scheme

*BasePath* : /callback/v1

*Schemes* : HTTP, HTTPS

## Consumes

- `application/json`

## Produces

- `application/json`

## External Docs

*Description* : ETSI GS NFV-SOL 005 V2.5.1

*URL* : [https://www.etsi.org/deliver/etsi\\_gs/NFV-SOL/001\\_099/005/02.05.01\\_60/gs\\_NFV-SOL005v020501p.pdf](https://www.etsi.org/deliver/etsi_gs/NFV-SOL/001_099/005/02.05.01_60/gs_NFV-SOL005v020501p.pdf)

## Paths

### Notify about PM related events

POST

/URI\_is\_provided\_by\_the\_client\_when\_creating\_the\_subscription\_PerformanceInformationAvailableNotification

## Description

The POST method delivers a notification regarding a performance management event from the API producer to an API consumer. The API consumer shall have previously created an "individual subscription resource" with a matching filter. This method shall follow the provisions specified in the Tables 7.4.9.3.1-1 and 7.4.9.3.1-2 for URI query parameters, request and response data structures, and response codes.

## Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	<b>Content-Type</b> <i>required</i>	The MIME type of the body of the request. Reference: IETF RFC 7231	string
Header	<b>Version</b> <i>required</i>	Version of the API requested to use when responding to this request.	string
Body	<b>PerformanceInformationAvailableNotification</b> <i>required</i>	Notification about performance information availability.	<a href="#">PerformanceInformationAvailableNotification</a>

## PerformanceInformationAvailableNotification

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this notification.	<a href="#">_links</a>
<b>id</b> <i>required</i>	An identifier with the intention of being globally unique.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "PerformanceInformationAvailableNotification" for this notification type.	string

Name	Description	Schema
<b>objectId</b> <i>required</i>	An identifier with the intention of being globally unique.	string
<b>subscriptionId</b> <i>required</i>	An identifier with the intention of being globally unique.	string

## links

Name	Description	Schema
<b>objectInstance</b> <i>optional</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">objectInstance</a>
<b>performanceReport</b> <i>required</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">performanceReport</a>
<b>pmJob</b> <i>required</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">pmJob</a>
<b>subscription</b> <i>required</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">subscription</a>

## **objectInstance**

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

## **performanceReport**

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

## pmJob

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

## subscription

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

## Responses

HTTP Code	Description	Schema
204	204 NO CONTENT Shall be returned when the notification was delivered successfully. <b>Headers :</b> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. <b>Version</b> (string) : Version of the API used in the response.	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 400

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 401</a></p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 403</a></p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 406



HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 503

### Response 400

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 401

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 403

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 404

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 405

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 406

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 500

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 503

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

## Test the notification endpoint

```
GET
/URI_is_provided_by_the_client_when_creating_the_subscription_PerformanceInformationAv
ailableNotificatio
```

### Description

The GET method allows the server to test the notification endpoint that is provided by the client, e.g. during subscription. This method shall follow the provisions specified in the Tables 7.4.9.3.2-1 and 7.4.9.3.2-2 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231.	string

Type	Name	Description	Schema
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	<b>Version</b> <i>required</i>	Version of the API requested to use when responding to this request.	string

## Responses

HTTP Code	Description	Schema
204	<p>204 NO CONTENT Shall be returned to indicate that the notification endpoint has been tested successfully. The response body shall be empty.</p> <p><b>Headers :</b></p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	No Content



HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 400

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 401</a></p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 403</a></p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 503

### Response 400

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 401

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 403

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 404

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 405

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 406

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string



Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 500

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 503

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

## Notify about PM related events

```
POST
/URI_is_provided_by_the_client_when_creating_the_subscription_ThresholdCrossedNotifica
tion
```

### Description

The POST method delivers a notification regarding a performance management event from the API producer to an API consumer. The API consumer shall have previously created an "individual subscription resource" with a matching filter. This method shall follow the provisions specified in the Tables 7.4.9.3.1-1 and 7.4.9.3.1-2 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	<b>Content-Type</b> <i>required</i>	The MIME type of the body of the request. Reference: IETF RFC 7231	string
Header	<b>Version</b> <i>required</i>	Version of the API requested to use when responding to this request.	string
Body	<b>ThresholdCrossedNotification</b> <i>required</i>	Notification about threshold crossing.	<a href="#">ThresholdCrossedNotification</a>

### ThresholdCrossedNotification

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this notification.	<a href="#">_links</a>
<b>crossingDirection</b> <i>required</i>	The enumeration CrossingDirectionType shall comply with the provisions. Acceptable Values are: UP - The threshold was crossed in upward direction. DOWN - The threshold was crossed in downward direction.	enum (UP, DOWN)
<b>id</b> <i>required</i>	An identifier with the intention of being globally unique.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "ThresholdCrossedNotification " for this notification type.	string
<b>objectInstanceid</b> <i>required</i>	An identifier with the intention of being globally unique.	string
<b>performanceMetric</b> <i>required</i>	Performance metric associated with the threshold. This attribute shall contain the related "Measurement Name" value as defined in clause 7.2 of ETSI GS NFV-IFA 027.	string

Name	Description	Schema
<b>performanceValue</b> <i>required</i>	Value of the metric that resulted in threshold crossing. The type of this attribute shall correspond to the related "Measurement Unit" as defined in clause 7.2 of ETSI GS NFV-IFA 027.	object
<b>subscriptionId</b> <i>required</i>	An identifier with the intention of being globally unique.	string
<b>thresholdId</b> <i>required</i>	An identifier with the intention of being globally unique.	string

### links

Name	Description	Schema
<b>objectInstance</b> <i>required</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">objectInstance</a>
<b>subscription</b> <i>required</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">subscription</a>
<b>threshold</b> <i>required</i>	This type represents a link to a resource in a notification, using an absolute or relative URI.	<a href="#">threshold</a>

### **objectInstance**

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

### **subscription**

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

## threshold

Name	Description	Schema
<b>href</b> <i>required</i>	URI of a resource referenced from a notification. Should be an absolute URI (i.e. a URI that contains {apiRoot}), however, may be a relative URI (i.e. a URI where the {apiRoot} part is omitted) if the {apiRoot} information is not available.	string (url)

## Responses

HTTP Code	Description	Schema
<b>204</b>	<p>204 NO CONTENT Shall be returned when the notification was delivered successfully.</p> <p><b>Headers :</b></p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	No Content

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 400</a></p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 401</a></p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 403</a></p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 406



HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 503

## Response 400

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 401

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 403

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 404

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 405

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 406

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 500

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 503

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

## Test the notification endpoint

```
GET
/URI_is_provided_by_the_client_when_creating_the_subscription_ThresholdCrossedNotifica
tion
```

### Description

The GET method allows the server to test the notification endpoint that is provided by the client, e.g. during subscription. This method shall follow the provisions specified in the Tables 7.4.9.3.2-1 and 7.4.9.3.2-2 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. Reference: IETF RFC 7231.	string

Type	Name	Description	Schema
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Reference: IETF RFC 7235	string
Header	<b>Version</b> <i>required</i>	Version of the API requested to use when responding to this request.	string

## Responses

HTTP Code	Description	Schema
204	<p>204 NO CONTENT Shall be returned to indicate that the notification endpoint has been tested successfully. The response body shall be empty.</p> <p><b>Headers :</b></p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	No Content



HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be properly specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 400</a></p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 401</a></p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	<p><a href="#">Response 403</a></p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>	Response 503

### Response 400

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 401

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 403

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 404

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 405

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

#### Response 406

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string



Name	Description	Schema
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 500

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

### Response 503

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>instance</b> <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
<b>type</b> <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)