

SOL005 - API version interface

Overview

SOL005 - API version Interface IMPORTANT: Please note that this file might be not aligned to the current version of the ETSI Group Specification it refers to and has not been approved by the ETSI NFV ISG. In case of discrepancies the published ETSI Group Specification takes precedence. Please report bugs to <https://forge.etsi.org/bugzilla/buglist.cgi?component=Nfv-Openapis>

Version information

Version : 1.1.0-impl:etsi.org:ETSI_NFV_OpenAPI:1

Contact information

Contact : NFV-SOL WG

License information

License : ETSI Forge copyright notice

License URL : <https://forge.etsi.org/etsi-forge-copyright-notice.txt>

Terms of service : null

URI scheme

Schemes : HTTP, HTTPS

Consumes

- `application/json`

Produces

- `application/json`

External Docs

Description : ETSI GS NFV-SOL 005 V2.5.1

URL : https://www.etsi.org/deliver/etsi_gs/NFV-SOL/001_099/005/02.05.01_60/gs_NFV-SOL005v020501p.pdf

Paths

Retrieve API version information

GET /nsd/api-versions

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
200	API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version.	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 404</p>
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 405</p>
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 406</p>

HTTP Code	Description	Schema
413	<p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 413
414	<p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 414
416	<p>416 RANGE NOT SATISFIABLE</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
429	<p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 429</p>

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
apiVersions <i>required</i>	Version(s) supported for the API signalled by the uriPrefix attribute.	< apiVersions > array
uriPrefix <i>required</i>	Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/.	string

apiVersions

Name	Description	Schema
isDeprecated <i>optional</i>	The Boolean is a data type having two values (TRUE and FALSE).	boolean
version <i>required</i>	Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 413

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 414

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 429

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Retrieve API version information

```
GET /nsfm/api-versions
```

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
200	API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version.	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
413	<p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 413
414	<p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 414
416	<p>416 RANGE NOT SATISFIABLE</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
429	<p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 429</p>

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
apiVersions <i>required</i>	Version(s) supported for the API signalled by the uriPrefix attribute.	< apiVersions > array
uriPrefix <i>required</i>	Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/.	string

apiVersions

Name	Description	Schema
isDeprecated <i>optional</i>	The Boolean is a data type having two values (TRUE and FALSE).	boolean
version <i>required</i>	Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 413

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 414

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 429

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Retrieve API version information

```
GET /nslcm/api-versions
```

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
200	API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version.	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
413	<p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 413
414	<p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 414
416	<p>416 RANGE NOT SATISFIABLE</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
429	<p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 429</p>

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
apiVersions <i>required</i>	Version(s) supported for the API signalled by the uriPrefix attribute.	< apiVersions > array
uriPrefix <i>required</i>	Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/.	string

apiVersions

Name	Description	Schema
isDeprecated <i>optional</i>	The Boolean is a data type having two values (TRUE and FALSE).	boolean
version <i>required</i>	Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 413

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 414

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 429

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Retrieve API version information

```
GET /nspm/api-versions
```

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
200	API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version.	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
413	<p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 413
414	<p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 414
416	<p>416 RANGE NOT SATISFIABLE</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
429	<p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 429</p>

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
apiVersions <i>required</i>	Version(s) supported for the API signalled by the uriPrefix attribute.	< apiVersions > array
uriPrefix <i>required</i>	Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/.	string

apiVersions

Name	Description	Schema
isDeprecated <i>optional</i>	The Boolean is a data type having two values (TRUE and FALSE).	boolean
version <i>required</i>	Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 413

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 414

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 429

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Retrieve API version information

```
GET /vnfpkgm/api-versions
```

Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

Parameters

Type	Name	Description	Schema
Header	Version <i>optional</i>	Version of the API requested to use when responding to this request.	string

Responses

HTTP Code	Description	Schema
200	API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13. Headers : Content-Type (string) : The MIME type of the body of the response. Version (string) : The used API version.	Response 200

HTTP Code	Description	Schema
400	<p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 400</p>

HTTP Code	Description	Schema
401	<p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 401</p>
403	<p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 403</p>

HTTP Code	Description	Schema
404	<p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 404
405	<p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 405
406	<p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p>Headers : Content-Type (string) : The MIME type of the body of the response. WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token. Version (string) : Version of the API used in the response.</p>	Response 406

HTTP Code	Description	Schema
413	<p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 413
414	<p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 414
416	<p>416 RANGE NOT SATISFIABLE</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 416

HTTP Code	Description	Schema
422	<p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 422</p>
429	<p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	<p>Response 429</p>

HTTP Code	Description	Schema
500	<p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 500
503	<p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 503
504	<p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p>Headers :</p> <p>Content-Type (string) : The MIME type of the body of the response.</p> <p>WWW-Authenticate (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p>Version (string) : Version of the API used in the response.</p>	Response 504

Response 200

Name	Description	Schema
apiVersions <i>required</i>	Version(s) supported for the API signalled by the uriPrefix attribute.	< apiVersions > array
uriPrefix <i>required</i>	Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/.	string

apiVersions

Name	Description	Schema
isDeprecated <i>optional</i>	The Boolean is a data type having two values (TRUE and FALSE).	boolean
version <i>required</i>	Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1.	string

Response 400

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 401

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 403

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 404

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 405

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 406

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 413

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 414

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 416

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 422

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 429

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string

Name	Description	Schema
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 500

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer

Name	Description	Schema
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 503

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string

Name	Description	Schema
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)

Response 504

Name	Description	Schema
detail <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
instance <i>optional</i>	A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.	string (URI)
status <i>required</i>	The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.	integer
title <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4).	string
type <i>optional</i>	A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".	string (URI)