

# SOL005 - API version interface

## Overview

SOL005 - API version Interface IMPORTANT: Please note that this file might be not aligned to the current version of the ETSI Group Specification it refers to and has not been approved by the ETSI NFV ISG. In case of discrepancies the published ETSI Group Specification takes precedence. Please report bugs to <https://forge.etsi.org/bugzilla/buglist.cgi?component=Nfv-Openapis>

## Version information

*Version* : 1.0.0-impl:etsi.org:ETSI\_NFV\_OpenAPI:1

## Contact information

*Contact* : NFV-SOL WG

## License information

*License* : ETSI Forge copyright notice

*License URL* : <https://forge.etsi.org/etsi-forge-copyright-notice.txt>

*Terms of service* : null

## URI scheme

*Schemes* : HTTP, HTTPS

## Consumes

- `application/json`

## Produces

- `application/json`

## External Docs

*Description* : ETSI GS NFV-SOL 005 V2.7.1

*URL* : [https://www.etsi.org/deliver/etsi\\_gs/NFV-SOL/001\\_099/005/02.07.01\\_60/gs\\_NFV-SOL005v020701p.pdf](https://www.etsi.org/deliver/etsi_gs/NFV-SOL/001_099/005/02.07.01_60/gs_NFV-SOL005v020701p.pdf)

# Paths

## POST /nsd/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced. | string (URI) |

| Name                             | Description   | Schema       |
|----------------------------------|---|--------------|
| <b>status</b><br><i>required</i> | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>  | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>   | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## Retrieve API version information

GET /nsd/api\_versions

### Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema       |
|-----------|---|--------------|
| 200       | <p>API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13.</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>Version</b> (string) : The used API version.</p>   | Response 200 |
| 400       | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p> | Response 400 |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 401       | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 401</a></p> |
| 403       | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 403</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 404       | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 404</a></p> |
| 406       | <p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 406</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 413       | <p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p> | Response 413 |
| 414       | <p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p>  | Response 414 |
| 416       | <p>416 RANGE NOT SATISFIABLE</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p>  | Response 416 |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 422       | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 422</a></p> |
| 429       | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 429</a></p> |



| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 500       | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 500 |
| 503       | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>                        | Response 503 |
| 504       | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 504 |

## Response 200

| Name                                  | Description   | Schema                                   |
|---------------------------------------|---|--|
| <b>apiVersions</b><br><i>required</i> | Version(s) supported for the API signalled by the uriPrefix attribute.                              | < <a href="#">apiVersions</a> ><br>array |
| <b>uriPrefix</b><br><i>required</i>   | Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/. | string                                   |

### apiVersions

| Name                                   | Description  | Schema  |
|--|--|---------|
| <b>isDeprecated</b><br><i>optional</i> | The Boolean is a data type having two values (TRUE and FALSE).   | boolean |
| <b>version</b><br><i>required</i>      | Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1. | string  |

### Response 400

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 401

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 403

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 404

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 406

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 413

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 414

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 416

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

## Response 422

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |



| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 429

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 500

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 503

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 504

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

## PUT /nsd/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code  | Description   | Schema                       |
|------------|---|------------------------------|
| <b>405</b> | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## DELETE /nsd/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# PATCH /nsd/api\_versions

## Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

## Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer      |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## POST /nsfm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses



| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# Retrieve API version information

GET /nsfm/api\_versions

## Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description  | Schema                       |
|-----------|--|------------------------------|
| 200       | API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13.<br><b>Headers :</b><br><b>Content-Type</b> (string) : The MIME type of the body of the response.<br><b>Version</b> (string) : The used API version. | <a href="#">Response 200</a> |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 400       | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 400</a></p> |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 401       | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 401</a></p> |
| 403       | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 403</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 404       | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 404</a></p> |
| 406       | <p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 406</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 413       | <p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 413 |
| 414       | <p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 414 |
| 416       | <p>416 RANGE NOT SATISFIABLE</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 416 |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 422       | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 422</a></p> |
| 429       | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 429</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 500       | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 500 |
| 503       | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>                        | Response 503 |
| 504       | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 504 |

## Response 200



| Name                                  | Description   | Schema                                   |
|---------------------------------------|---|--|
| <b>apiVersions</b><br><i>required</i> | Version(s) supported for the API signalled by the uriPrefix attribute.                              | < <a href="#">apiVersions</a> ><br>array |
| <b>uriPrefix</b><br><i>required</i>   | Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/. | string                                   |

### apiVersions

| Name                                   | Description  | Schema  |
|--|--|---------|
| <b>isDeprecated</b><br><i>optional</i> | The Boolean is a data type having two values (TRUE and FALSE).   | boolean |
| <b>version</b><br><i>required</i>      | Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1. | string  |

### Response 400

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 401

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 403

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 404

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

#### Response 406

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 413

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 414

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 416

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

## Response 422

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 429

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 500

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |



| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 503

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 504

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

## PUT /nsfm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code  | Description   | Schema                       |
|------------|---|------------------------------|
| <b>405</b> | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## DELETE /nsfm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# PATCH /nsfm/api\_versions

## Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

## Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer      |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## POST /nslcm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |



# Retrieve API version information

GET /nslcm/api\_versions

## Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description  | Schema                       |
|-----------|--|------------------------------|
| 200       | API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13.<br><b>Headers :</b><br><b>Content-Type</b> (string) : The MIME type of the body of the response.<br><b>Version</b> (string) : The used API version. | <a href="#">Response 200</a> |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 400       | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 400</a></p> |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 401       | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 401</a></p> |
| 403       | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 403</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 404       | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 404</a></p> |
| 406       | <p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 406</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 413       | <p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 413 |
| 414       | <p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 414 |
| 416       | <p>416 RANGE NOT SATISFIABLE</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 416 |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 422       | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 422</a></p> |
| 429       | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 429</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 500       | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 500 |
| 503       | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>                        | Response 503 |
| 504       | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 504 |

## Response 200

| Name                                  | Description   | Schema                                   |
|---------------------------------------|---|--|
| <b>apiVersions</b><br><i>required</i> | Version(s) supported for the API signalled by the uriPrefix attribute.                              | < <a href="#">apiVersions</a> ><br>array |
| <b>uriPrefix</b><br><i>required</i>   | Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/. | string                                   |

### apiVersions

| Name                                   | Description  | Schema  |
|--|--|---------|
| <b>isDeprecated</b><br><i>optional</i> | The Boolean is a data type having two values (TRUE and FALSE).   | boolean |
| <b>version</b><br><i>required</i>      | Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1. | string  |

### Response 400

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |



| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 401

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 403

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 404

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 406

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 413

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 414

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 416

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

## Response 422

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

#### Response 429

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

#### Response 500

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 503

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |



| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 504

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

## PUT /nslcm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code  | Description   | Schema                       |
|------------|---|------------------------------|
| <b>405</b> | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## DELETE /nslcm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# PATCH /nslcm/api\_versions

## Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

## Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer      |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## POST /nspm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# Retrieve API version information

GET /nspm/api\_versions

## Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description  | Schema                       |
|-----------|--|------------------------------|
| 200       | API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13.<br><b>Headers :</b><br><b>Content-Type</b> (string) : The MIME type of the body of the response.<br><b>Version</b> (string) : The used API version. | <a href="#">Response 200</a> |



| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 400       | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 400</a></p> |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 401       | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 401</a></p> |
| 403       | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 403</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 404       | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 404</a></p> |
| 406       | <p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 406</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 413       | <p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p> | Response 413 |
| 414       | <p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p>  | Response 414 |
| 416       | <p>416 RANGE NOT SATISFIABLE</p> <p><b>Headers :</b><br/> <b>Content-Type</b> (string) : The MIME type of the body of the response.<br/> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.<br/> <b>Version</b> (string) : Version of the API used in the response.</p>  | Response 416 |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 422       | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 422</a></p> |
| 429       | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 429</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 500       | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 500 |
| 503       | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>                        | Response 503 |
| 504       | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 504 |

## Response 200

| Name                                  | Description   | Schema                                   |
|---------------------------------------|---|--|
| <b>apiVersions</b><br><i>required</i> | Version(s) supported for the API signalled by the uriPrefix attribute.                              | < <a href="#">apiVersions</a> ><br>array |
| <b>uriPrefix</b><br><i>required</i>   | Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/. | string                                   |

### apiVersions

| Name                                   | Description  | Schema  |
|--|--|---------|
| <b>isDeprecated</b><br><i>optional</i> | The Boolean is a data type having two values (TRUE and FALSE).   | boolean |
| <b>version</b><br><i>required</i>      | Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1. | string  |

### Response 400

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 401

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 403

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |



| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 404

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 406

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 413

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 414

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 416

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## Response 422

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 429

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 500

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 503

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

#### Response 504

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |



| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

## PUT /nspm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code  | Description   | Schema                       |
|------------|---|------------------------------|
| <b>405</b> | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## DELETE /nspm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# PATCH /nspm/api\_versions

## Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

## Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer      |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## POST /vnfpkgm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# Retrieve API version information

GET /vnfpkgm/api\_versions

## Description

The GET method reads API version information. This method shall follow the provisions specified in table 4.6.3.3.3.2-1 for request and response data structures, and response codes. URI query parameters are not supported.

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description  | Schema                       |
|-----------|--|------------------------------|
| 200       | API version information was read successfully. The response body shall contain 4.4 API version information, as defined in clause 4.4.1.13.<br><b>Headers :</b><br><b>Content-Type</b> (string) : The MIME type of the body of the response.<br><b>Version</b> (string) : The used API version. | <a href="#">Response 200</a> |

| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 400       | <p>400 BAD REQUEST 400 code can be returned in the following specified cases, the specific cause has to be proper specified in the "ProblemDetails" structure to be returned. If the request is malformed or syntactically incorrect (e.g. if the request URI contains incorrect query parameters or the payload body contains a syntactically incorrect data structure), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If the response to a GET request which queries a container resource would be so big that the performance of the API producer is adversely affected, and the API producer does not support paging for the affected resource, it shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. If there is an application error related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem. If the request contains a malformed access token, the API producer should respond with this response. The details of the error shall be returned in the WWW Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided. The use of this HTTP error response code described above is applicable to the use of the OAuth 2.0 for the authorization of API requests and notifications, as defined in clauses 4.5.3.3 and 4.5.3.4.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 400</a></p> |



| HTTP Code | Description   | Schema                              |
|-----------|---|-------------------------------------|
| 401       | <p>401 UNAUTHORIZED If the request contains no access token even though one is required, or if the request contains an authorization token that is invalid (e.g. expired or revoked), the API producer should respond with this response. The details of the error shall be returned in the WWW-Authenticate HTTP header, as defined in IETF RFC 6750 and IETF RFC 7235. The ProblemDetails structure may be provided.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 401</a></p> |
| 403       | <p>403 FORBIDDEN If the API consumer is not allowed to perform a particular request to a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided. It should include in the "detail" attribute information about the source of the problem, and may indicate how to solve it.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 403</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 404       | <p>404 NOT FOUND If the API producer did not find a current representation for the resource addressed by the URI passed in the request or is not willing to disclose that one exists, it shall respond with this response code. The "ProblemDetails" structure may be provided, including in the "detail" attribute information about the source of the problem, e.g. a wrong resource URI variable. This response code is not appropriate in case the resource addressed by the URI is a container resource which is designed to contain child resources, but does not contain any child resource at the time the request is received. For a GET request to an existing empty container resource, a typical response contains a 200 OK response code and a payload body with an empty array.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 404</a></p> |
| 406       | <p>406 NOT ACCEPTABLE If the "Accept" header does not contain at least one name of a content type that is acceptable to the API producer, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 406</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 413       | <p>413 PAYLOAD TOO LARGE If the payload body of a request is larger than the amount of data the API producer is willing or able to process, it shall respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for closing the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 413</a></p> |
| 414       | <p>414 URI TOO LONG If the request URI of a request is longer than the API producer is willing or able to process, it shall respond with this response code. This condition can e.g. be caused by passing long queries in the request URI of a GET request. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 414</a></p> |
| 416       | <p>416 RANGE NOT SATISFIABLE</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | <p><a href="#">Response 416</a></p> |

| HTTP Code | Description  | Schema                              |
|-----------|--|-------------------------------------|
| 422       | <p>422 UNPROCESSABLE ENTITY If the payload body of a request contains syntactically correct data (e.g. well-formed JSON) but the data cannot be processed (e.g. because it fails validation against a schema), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and should include in the "detail" attribute more information about the source of the problem. This error response code is only applicable for methods that have a request body.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>   | <p><a href="#">Response 422</a></p> |
| 429       | <p>429 TOO MANY REQUESTS If the API consumer has sent too many requests in a defined period of time and the API producer is able to detect that condition ("rate limiting"), the API producer shall respond with this response code, following the provisions in IETF RFC 6585 [17] for the use of the "Retry-After" HTTP header. The "ProblemDetails" structure shall be provided and shall include in the "detail" attribute more information about the source of the problem. The period of time and allowed number of requests are configured within the API producer by means outside the scope of the present document.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <p><a href="#">Response 429</a></p> |

| HTTP Code | Description  | Schema       |
|-----------|--|--------------|
| 500       | <p>500 INTERNAL SERVER ERROR If there is an application error not related to the client's input that cannot be easily mapped to any other HTTP response code ("catch all error"), the API producer shall respond with this response code. The "ProblemDetails" structure shall be provided, and shall include in the "detail" attribute more information about the source of the problem.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | Response 500 |
| 503       | <p>503 SERVICE UNAVAILABLE If the API producer encounters an internal overload situation of itself or of a system it relies on, it should respond with this response code, following the provisions in IETF RFC 7231 for the use of the "Retry-After" HTTP header and for the alternative to refuse the connection. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>                        | Response 503 |
| 504       | <p>504 GATEWAY TIMEOUT If the API producer encounters a timeout while waiting for a response from an upstream server (i.e. a server that the API producer communicates with when fulfilling a request), it should respond with this response code.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p>  | Response 504 |

## Response 200

| Name                                  | Description   | Schema                                   |
|---------------------------------------|---|--|
| <b>apiVersions</b><br><i>required</i> | Version(s) supported for the API signalled by the uriPrefix attribute.                              | < <a href="#">apiVersions</a> ><br>array |
| <b>uriPrefix</b><br><i>required</i>   | Specifies the URI prefix for the API, in the following form {apiRoot}/{apiName}/{apiMajorVersion}/. | string                                   |

### apiVersions

| Name                                   | Description  | Schema  |
|--|--|---------|
| <b>isDeprecated</b><br><i>optional</i> | The Boolean is a data type having two values (TRUE and FALSE).   | boolean |
| <b>version</b><br><i>required</i>      | Identifies a supported version. The value of the version attribute shall be a version identifier as specified in clause 4.6.1. | string  |

### Response 400

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 401

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 403

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 404

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |



| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 406

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 413

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 414

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 416

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

## Response 422

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

### Response 429

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

### Response 500

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

### Response 503

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer       |

| <b>Name</b>                     | <b>Description</b>  | <b>Schema</b> |
|---------------------------------|---|---------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI)  |

#### Response 504

| <b>Name</b>                        | <b>Description</b>  | <b>Schema</b> |
|------------------------------------|---|---------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string        |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI)  |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer       |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string        |

| Name                           | Description  | Schema       |
|--------------------------------|--|--------------|
| <b>type</b><br><i>optional</i> | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank". | string (URI) |

## PUT /vnfpkgm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code  | Description   | Schema                       |
|------------|---|------------------------------|
| <b>405</b> | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                             | Description  | Schema |
|----------------------------------|--|--------|
| <b>detail</b><br><i>required</i> | A human-readable explanation specific to this occurrence of the problem. | string |



| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

## DELETE /vnfpkgm/api\_versions

### Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

### Parameters

| Type          | Name                              | Description  | Schema |
|---------------|-----------------------------------|--|--------|
| <b>Header</b> | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

### Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

### Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem.   | integer      |
| <b>title</b><br><i>optional</i>    | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>     | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |

# PATCH /vnfpkgm/api\_versions

## Description

This method is not supported. When this method is requested on this resource, the API producer shall return a "405 Method Not Allowed" response

## Parameters

| Type   | Name                              | Description  | Schema |
|--------|-----------------------------------|--|--------|
| Header | <b>Version</b><br><i>optional</i> | Version of the API requested to use when responding to this request. | string |

## Responses

| HTTP Code | Description   | Schema                       |
|-----------|---|------------------------------|
| 405       | <p>405 METHOD NOT ALLOWED If a particular HTTP method is not supported for a particular resource, the API producer shall respond with this response code. The "ProblemDetails" structure may be omitted.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Version</b> (string) : Version of the API used in the response.</p> | <a href="#">Response 405</a> |

## Response 405

| Name                               | Description   | Schema       |
|------------------------------------|---|--------------|
| <b>detail</b><br><i>required</i>   | A human-readable explanation specific to this occurrence of the problem.  | string       |
| <b>instance</b><br><i>optional</i> | A URI reference that identifies the specific occurrence of the problem. It may yield further information if dereferenced.   | string (URI) |
| <b>status</b><br><i>required</i>   | The HTTP status code for this occurrence of the problem. The HTTP status code ([RFC7231], Section 6) generated by the origin server for this occurrence of the problem. | integer      |

| Name                            | Description   | Schema       |
|---------------------------------|---|--------------|
| <b>title</b><br><i>optional</i> | A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided. A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localization (e.g., using proactive content negotiation; see [RFC7231], Section 3.4). | string       |
| <b>type</b><br><i>optional</i>  | A URI reference according to IETF RFC 3986 [5] that identifies the problem type. It is encouraged that the URI provides human-readable documentation for the problem (e.g. using HTML) when dereferenced. When this member is not present, its value is assumed to be "about:blank".  | string (URI) |