

DRAFT - SOL005 - NSD Management  
Interface

# Overview

DRAFT - SOL005 - NSD Management Interface IMPORTANT: Please note that this file might be not aligned to the current version of the ETSI Group Specification it refers to and has not been approved by the ETSI NFV ISG. In case of discrepancies the published ETSI Group Specification takes precedence. Please report bugs to <https://forge.etsi.org/bugzilla/buglist.cgi?component=Nfv-Openapis>

## Version information

*Version* : 2.4.1

## Contact information

*Contact* : NFV-SOL WG

## License information

*License* : ETSI Forge copyright notice

*License URL* : <https://forge.etsi.org/etsi-forge-copyright-notice.txt>

*Terms of service* : null

## Consumes

- `application/json`

## Produces

- `application/json`

## Paths

### Create NSD Info

POST /ns\_descriptors

### Description

The POST method is used to create a new NS descriptor resource. This method shall follow the provisions specified in the Tables 5.4.2.3.1-1 and 5.4.2.3.1-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

## Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>optional</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005	string
Header	<b>Content-Type</b> <i>optional</i>	The MIME type of the body of the request. This header field shall be present if the request has a non-empty message body.	string
Body	<b>body</b> <i>required</i>		<a href="#">body</a>

### body

Name	Description	Schema
<b>CreateNsdInfo Request</b> <i>required</i>	This type creates a completely new NS descriptor resource.	<a href="#">CreateNsdInfoRequest</a>

### CreateNsdInfoRequest

Name	Description	Schema
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object

## Responses

HTTP Code	Description	Schema
201	<p>Status 201</p> <p><b>Headers :</b></p> <p><b>Location</b> (string) : The HTTP response shall include a "Location" HTTP header that contains the resource URI of the new NS descriptor resource.</p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	Response 201

### Response 201

Name	Description	Schema
<b>NsdInfo</b> <i>optional</i>	This type represents a response for the query NSD operation. It shall comply with the provisions defined in Table 5.5.2.2-1 of GS NFV-SOL 005.	<a href="#">NsdInfo</a>

### NsdInfo

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of the onboarded individual NS descriptor resource. This identifier is allocated by the NFVO.	string
<b>nestedNsdInfoIds</b> <i>optional</i>	Identifies the NsdInfo element for the nested NSD referenced by the on-boarded NS descriptor resource. At least one of the attributes – vnfPkgId and nestedNsdInfoId shall be present, after the NSD is on-boarded.	< string > array
<b>nsdDesigner</b> <i>optional</i>	Designer of the on-boarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies the NSD in a globally unique way. It is copied from the NSD content and shall be present after the NSD content is on-boarded.	object

Name	Description	Schema
<b>nsdInvariantId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies an NSD in a version independent manner. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdName</b> <i>optional</i>	Name of the onboarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdOnboardingState</b> <i>required</i>	The enumeration NsdOnboardingStateType shall comply with the provisions defined in Table 5.5.4.5-1 of GS NFV-SOL 005. It indicates the onboarding state of the NSD.  CREATED = The NSD information object is created. UPLOADING = The associated NSD content is being uploaded. PROCESSING = The associated NSD content is being processed, e.g. validation. ONBOARDED = The associated NSD content is on-boarded.	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED)
<b>nsdOperationalState</b> <i>required</i>	The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV-SOL 005. It indicates the operational state of the resource.  ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.	enum (ENABLED, DISABLED)
<b>nsdUsageState</b> <i>required</i>	The enumeration NsdUsageStateType shall comply with the provisions defined in Table 5.5.4.4-1 of GS NFV-SOL 005. It indicates the usage state of the resource.  IN_USE = The resource is in use. NOT_IN_USE = The resource is not-in-use.	enum (IN_USE, NOT_IN_USE)
<b>nsdVersion</b> <i>optional</i>	Version of the on-boarded NSD. The NSD version is a string of variable length. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string

Name	Description	Schema
<b>onboardingFailureDetails</b> <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>
<b>pnfdInfoIds</b> <i>optional</i>	Identifies the PnfdInfo element for the PNFD referenced by the on-boarded NS descriptor resource.	< string > array
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object
<b>vnfPkgIds</b> <i>optional</i>	Identifies the VNF package for the VNFD referenced by the on-boarded NS descriptor resource.	< string > array

### \_links

Name	Description	Schema
<b>nsd_content</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **onboardingFailureDetails**

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Query NSD Info

```
GET /ns_descriptors
```

### Description

The GET method queries information about multiple NS descriptor resources. This method shall follow the provisions specified in the Tables 5.4.2.3.2-1 and 5.4.2.3.2-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	This header field shall be present if the response is expected to have a non-empty message body.	string
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string

### Responses

HTTP Code	Description	Schema
200	<p>Information about zero or more NS descriptors. The response body shall contain a representation of zero or more NS descriptors, as defined in clause 5.5.2.2 of GS NFV-SOL 005.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	Response 200
400	<p>There are two possible scenarios listed below.</p> <p>Error: Invalid attribute-based filtering parameters.</p> <p>The response body shall contain a ProblemDetails structure, in which the "detail" attribute should convey more information about the error.</p> <p>Error: Invalid attribute selector. The response body shall contain a ProblemDetails structure, in which the "detail" attribute should convey more information about the error.</p>	No Content

### Response 200

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of the onboarded individual NS descriptor resource. This identifier is allocated by the NFVO.	string
<b>nestedNsdInfoIds</b> <i>optional</i>	Identifies the NsdInfo element for the nested NSD referenced by the on-boarded NS descriptor resource. At least one of the attributes – vnfPkgId and nestedNsdInfoId shall be present, after the NSD is on-boarded.	< string > array
<b>nsdDesigner</b> <i>optional</i>	Designer of the on-boarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string



Name	Description	Schema
<b>nsdId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies the NSD in a globally unique way. It is copied from the NSD content and shall be present after the NSD content is on-boarded.	object
<b>nsdInvariantId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies an NSD in a version independent manner. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdName</b> <i>optional</i>	Name of the onboarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdOnboardingState</b> <i>required</i>	<p>The enumeration NsdOnboardingStateType shall comply with the provisions defined in Table 5.5.4.5-1 of GS NFV-SOL 005. It indicates the onboarding state of the NSD.</p> <p>CREATED = The NSD information object is created.          UPLOADING = The associated NSD content is being uploaded.          PROCESSING = The associated NSD content is being processed, e.g. validation.          ONBOARDED = The associated NSD content is on-boarded.</p>	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED)
<b>nsdOperationalState</b> <i>required</i>	<p>The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV-SOL 005. It indicates the operational state of the resource.</p> <p>ENABLED = The operational state of the resource is enabled.          DISABLED = The operational state of the resource is disabled.</p>	enum (ENABLED, DISABLED)
<b>nsdUsageState</b> <i>required</i>	<p>The enumeration NsdUsageStateType shall comply with the provisions defined in Table 5.5.4.4-1 of GS NFV-SOL 005. It indicates the usage state of the resource.</p> <p>IN_USE = The resource is in use.          NOT_IN_USE = The resource is not-in-use.</p>	enum (IN_USE, NOT_IN_USE)
<b>nsdVersion</b> <i>optional</i>	Version of the on-boarded NSD. The NSD version is a string of variable length. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string

Name	Description	Schema
<b>onboardingFailureDetails</b> <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>
<b>pnfdInfoIds</b> <i>optional</i>	Identifies the PnfdInfo element for the PNFD referenced by the on-boarded NS descriptor resource.	< string > array
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object
<b>vnfPkgIds</b> <i>optional</i>	Identifies the VNF package for the VNFD referenced by the on-boarded NS descriptor resource.	< string > array

### \_links

Name	Description	Schema
<b>nsd_content</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **onboardingFailureDetails**

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Query NSD Info

```
GET /ns_descriptors/{nsdInfoId}
```

### Description

The GET method reads information about an individual NS descriptor. This method shall follow the provisions specified in GS NFV-SOL 005 Tables 5.4.3.3.2-1 and 5.4.3.3.2-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
<b>Path</b>	<b>nsdInfoId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
200	<p>Information about the individual NS descriptor. The response body shall contain a representation of the individual NS descriptor, as defined in clause 5.5.2.2 of GS NFV-SOL 005.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	<a href="#">Response 200</a>

### Response 200

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of the onboarded individual NS descriptor resource. This identifier is allocated by the NFVO.	string
<b>nestedNsdInfoIds</b> <i>optional</i>	Identifies the NsdInfo element for the nested NSD referenced by the on-boarded NS descriptor resource. At least one of the attributes – vnfPkgId and nestedNsdInfoId shall be present, after the NSD is on-boarded.	< string > array
<b>nsdDesigner</b> <i>optional</i>	Designer of the on-boarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies the NSD in a globally unique way. It is copied from the NSD content and shall be present after the NSD content is on-boarded.	object
<b>nsdInvariantId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies an NSD in a version independent manner. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string

Name	Description	Schema
<b>nsdName</b> <i>optional</i>	Name of the onboarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdOnboardingState</b> <i>required</i>	<p>The enumeration NsdOnboardingStateType shall comply with the provisions defined in Table 5.5.4.5-1 of GS NFV-SOL 005. It indicates the onboarding state of the NSD.</p> <p>CREATED = The NSD information object is created.          UPLOADING = The associated NSD content is being uploaded.          PROCESSING = The associated NSD content is being processed, e.g. validation.          ONBOARDED = The associated NSD content is on-boarded.</p>	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED)
<b>nsdOperationalState</b> <i>required</i>	<p>The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV-SOL 005. It indicates the operational state of the resource.</p> <p>ENABLED = The operational state of the resource is enabled.          DISABLED = The operational state of the resource is disabled.</p>	enum (ENABLED, DISABLED)
<b>nsdUsageState</b> <i>required</i>	<p>The enumeration NsdUsageStateType shall comply with the provisions defined in Table 5.5.4.4-1 of GS NFV-SOL 005. It indicates the usage state of the resource.</p> <p>IN_USE = The resource is in use.          NOT_IN_USE = The resource is not-in-use.</p>	enum (IN_USE, NOT_IN_USE)
<b>nsdVersion</b> <i>optional</i>	Version of the on-boarded NSD. The NSD version is a string of variable length. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string

Name	Description	Schema
<b>onboardingFailureDetails</b> <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>
<b>pnfdInfoIds</b> <i>optional</i>	Identifies the PnfdInfo element for the PNFD referenced by the on-boarded NS descriptor resource.	< string > array
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object
<b>vnfPkgIds</b> <i>optional</i>	Identifies the VNF package for the VNFD referenced by the on-boarded NS descriptor resource.	< string > array

### \_links

Name	Description	Schema
<b>nsd_content</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **onboardingFailureDetails**

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Delete NSD

```
DELETE /ns_descriptors/{nsdInfoId}
```

### Description

The DELETE method deletes an individual NS descriptor resource. An individual NS descriptor resource can only be deleted when there is no NS instance using it (i.e. `usageState = NOT_IN_USE`) and has been disabled already (i.e. `operationalState = DISABLED`). Otherwise, the DELETE method shall fail. This method shall follow the provisions specified in the Tables 5.4.3.3.5-1 and 5.4.3.3.5-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
<b>Path</b>	<b>nsdInfoId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
204	<p>The operation has completed successfully. The response body shall be empty.</p> <p><b>Headers :</b>  <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	object
409	Status 409	<a href="#">Response 409</a>

### Response 409

Name	Description	Schema
<b>ProblemDetails</b> <i>required</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">ProblemDetails</a>

### ProblemDetails

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object



Name	Description	Schema
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Update NSD Info

```
PATCH /ns_descriptors/{nsdInfoId}
```

### Description

The PATCH method modifies the operational state and/or user defined data of an individual NS descriptor resource. This method can be used to: 1) Enable a previously disabled individual NS descriptor resource, allowing again its use for instantiation of new network service with this descriptor. The usage state (i.e. "IN\_USE/NOT\_IN\_USE") shall not change as a result. 2) Disable a previously enabled individual NS descriptor resource, preventing any further use for instantiation of new network service(s) with this descriptor. The usage state (i.e. "IN\_USE/NOT\_IN\_USE") shall not change as a result. 3) Modify the user defined data of an individual NS descriptor resource. This method shall follow the provisions specified in the Tables 5.4.3.3.4-1 and 5.4.3.3.4-2 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3.	string
<b>Header</b>	<b>Content-Type</b> <i>required</i>	The MIME type of the body of the request. This header field shall be present if the request has a non-empty message body.	string

Type	Name	Description	Schema
Path	<b>nsdInfoId</b> <i>required</i>		string
Body	<b>body</b> <i>required</i>		<a href="#">body</a>

## body

Name	Description	Schema
<b>NsdInfoModifications</b> <i>required</i>	<p>This type represents attribute modifications for an individual NS descriptor resource based on the "NsdInfo" data type. The attributes of "NsdInfo" that can be modified are included in the "NsdInfoModifications" data type.</p> <p><b>NOTE</b> At least one of the attributes - nsdOperationalState and userDefinedData - shall be present.</p>	<a href="#">NsdInfoModifications</a>

## NsdInfoModifications

Name	Description	Schema
<b>nsdOperationalState</b> <i>optional</i>	<p>The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV_SOL 005. It indicates the operational state of the resource.</p> <p>ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.</p>	enum (ENABLED, DISABLED)
<b>userDefinedData</b> <i>optional</i>	<p>Modifications of the "userDefinedData" attribute in "NsdInfo" data type. See note. If present, these modifications shall be applied according to the rules of JSON Merge PATCH (see IETF RFC 7396 [25]). NOTE: At least one of the attributes - nsdOperationalState and userDefinedData - shall be present.</p>	object

## Responses

HTTP Code	Description	Schema
200	Status 200 <b>Headers :</b> <b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body. <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.	Response 200
409	Status 409	Response 409
412	Status 412	Response 412

### Response 200

Name	Description	Schema
<b>nsdOperationalState</b> <i>optional</i>	The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV_SOL 005. It indicates the operational state of the resource.  ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.	enum (ENABLED, DISABLED)
<b>userDefinedData</b> <i>optional</i>	Modifications of the "userDefinedData" attribute in "NsdInfo" data type. See note. If present, these modifications shall be applied according to the rules of JSON Merge PATCH (see IETF RFC 7396 [25]). NOTE: At least one of the attributes - nsdOperationalState and userDefinedData - shall be present.	object

### Response 409

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

Name	Description	Schema
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Response 412

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Get NSD Content

```
GET /ns_descriptors/{nsdInfoId}/nsd_content
```

### Description

The GET method fetches the content of the NSD.

The NSD can be implemented as a single file or as a collection of multiple files. If the NSD is

implemented in the form of multiple files, a ZIP file embedding these files shall be returned. If the NSD is implemented as a single file, either that file or a ZIP file embedding that file shall be returned.

The selection of the format is controlled by the "Accept" HTTP header passed in the GET request.

**NOTE** | The structure of the NSD zip file is outside the scope of the present document.

## Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	<p>String Required If the “Accept” header contains only “text/plain” and the NSD is implemented as a single file, the file shall be returned; otherwise, an error message shall be returned.</p> <p>If the “Accept” header contains only “application/zip”, the single file or the multiple files that make up the NSD shall be returned embedded in a ZIP file.</p> <p>If the “Accept” header contains both “text/plain” and “application/zip”, it is up to the NFVO to choose the format to return for a single-file NSD; for a multi-file NSD, a ZIP file shall be returned.</p>	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
Header	<b>Range</b> <i>optional</i>	<p>The request may contain a "Range" HTTP header to obtain single range of bytes from the NSD file. This can be used to continue an aborted transmission.</p> <p>If the NFVO does not support range requests, the NFVO shall ignore the 'Range" header, process the GET request, and return the whole NSD file with a 200 OK response (rather than returning a 4xx error status code).</p>	string
Path	<b>nsdInfoId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
200	<p>On success, the content of the NSD is returned. The payload body shall contain a copy of the file representing the NSD or a ZIP file that contains the file or multiple files representing the NSD, as specified above. The "Content-Type" HTTP header shall be set according to the format of the returned file, i.e. to "text/plain" for a YAML file or to "application/zip" for a ZIP file.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The "Content-Type" HTTP header shall be set according to the format of the returned file, i.e. to "text/plain" for a YAML file or to "application/zip" for a ZIP file.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Content-Range</b> (string) : Signals the byte range that is contained in the response, and the total length of the file.</p> <p><b>Accept-Ranges</b> (string) : Used by the server to signal whether or not it supports ranges for certain resources.</p>	object
206	<p>On success, if the NFVO supports range requests, a single consecutive byte range from the content of the NSD file is returned.</p> <p>The response body shall contain the requested part of the NSD file.</p> <p>The "Content-Range" HTTP header shall be provided according to IETF RFC 7233 [23].</p> <p>The "Content-Type" HTTP header shall be set as defined above for the "200 OK" response.</p> <p><b>Headers :</b></p> <p><b>Content-Range</b> (string)</p> <p><b>Content-Type</b> (string)</p>	No Content
406	Status 406	object
409	Status 409	object
416	Status 416	object

## Upload NSD

```
PUT /ns_descriptors/{nsdInfoId}/nsd_content
```

## Description

The PUT method is used to upload the content of a NSD. The NSD to be uploaded can be implemented as a single file or as a collection of multiple files, as defined in clause 5.4.4.3.2 of GS NFV-SOL 005. If the NSD is implemented in the form of multiple files, a ZIP file embedding these files shall be uploaded. If the NSD is implemented as a single file, either that file or a ZIP file embedding that file shall be uploaded. The "Content-Type" HTTP header in the PUT request shall be set accordingly based on the format selection of the NSD. If the NSD to be uploaded is a text file, the "Content-Type" header is set to "text/plain". If the NSD to be uploaded is a zip file, the "Content-Type" header is set to "application/zip". This method shall follow the provisions specified in the Tables 5.4.4.3.3-1 and 5.4.4.3.3-2 of GS-NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

## Parameters

Type	Name	Description	Schema
Header	<b>Content-Type</b> <i>optional</i>	The payload body contains a copy of the file representing the NSD or a ZIP file that contains the file or multiple files representing the NSD, as specified above. The request shall set the "Content-Type" HTTP header as defined above.	string
Path	<b>nsdInfoId</b> <i>required</i>		string
Body	<b>body</b> <i>required</i>		object

## Responses

HTTP Code	Description	Schema
202	Status 202	object
204	The NSD content was successfully uploaded and validated (synchronous mode). The response body shall be empty.	No Content
409	Error: The operation cannot be executed currently, due to a conflict with the state of the resource. Typically, this is due to the fact that the NsdOnboardingState has a value other than CREATED. The response body shall contain a ProblemDetails structure, in which the "detail" attribute shall convey more information about the error.	<a href="#">Response 409</a>

## Response 409

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Create PNF Info

POST /pnf\_descriptors

### Description

The POST method is used to create a new PNF descriptor resource.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS-NFV-SOL 005.	string
<b>Body</b>	<b>body</b> <i>required</i>		object



## Responses

HTTP Code	Description	Schema
201	Status 201 <b>Headers :</b> <b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body. <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.	object

## Query PFND Info

```
GET /pnf_descriptors
```

### Description

The GET method queries information about multiple PNF descriptor resources.

### Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>optional</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
Query	<b>all_fields</b> <i>optional</i>	Include all complex attributes in the response. See clause 4.3.3 for details. The NFVO shall support this parameter.	string

Type	Name	Description	Schema
Query	<b>exclude_default</b> It is optional	<p>Indicates to exclude the following complex attributes from the response. See clause 4.3.3 for details.</p> <p>The NFVO shall support this parameter.</p> <p>The following attributes shall be excluded from the PnfdInfo structure in the response body if this parameter is provided, or none of the parameters "all_fields," "fields", "exclude_fields", "exclude_default" are provided: userDefinedData.</p>	string

## Responses

HTTP Code	Description	Schema
200	<p>Status 200</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	object

## Query PNF Info

```
GET /pnf_descriptors/{pnfdInfoId}
```

### Description

The GET method reads information about an individual PNF descriptor. This method shall follow the provisions specified in the Tables 5.4.6.3.2-1 and 5.4.6.3.2-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3.	string
Path	<b>pnfdInfoId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
200	<p>Information about the individual PNF descriptor. The response body shall contain a representation of the individual PNF descriptor, as defined in clause 5.5.2.5 of GS NFV-SOL 005.</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	No Content

## Delete PNF

```
DELETE /pnf_descriptors/{pnfdInfoId}
```

### Description

The DELETE method deletes an individual PNF descriptor resource. An individual PNF descriptor resource can only be deleted when there is no NS instance using it or there is NSD referencing it. To delete all PNF versions identified by a particular value of the "pnfdInvariantId" attribute, the procedure is to first use the GET method with filter "pnfdInvariantId" towards the PNF descriptors resource to find all versions of the PNF. Then, the client uses the DELETE method described in this clause to delete each PNF version individually. This method shall follow the provisions specified in the Tables 5.4.6.3.5-1 and 5.4.6.3.5-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

## Parameters

Type	Name	Description	Schema
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3.	string
Path	<b>pnfdInfoId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
204	The operation has completed successfully. The response body shall be empty. <b>Headers :</b> <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.	No Content

## Update PNF Info

```
PATCH /pnf_descriptors/{pnfdInfoId}
```

## Description

The PATCH method modifies the user defined data of an individual PNF descriptor resource. This method shall follow the provisions specified in the Tables 5.4.6.3.4-1 and 5.4.6.3.4-2 for URI query parameters, request and response data structures, and response codes.

## Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non empty message body.	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3.	string

Type	Name	Description	Schema
Header	<b>Content-Type</b> <i>required</i>	The MIME type of the body of the request. This header field shall be present if the request has a non-empty message body.	string
Path	<b>pnfdInfoId</b> <i>required</i>		string
Body	<b>body</b> <i>required</i>		<a href="#">body</a>

## body

Name	Description	Schema
<b>userDefinedData</b> <i>required</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object

## Responses

HTTP Code	Description	Schema
<b>200</b>	Status 200 <b>Headers :</b> <b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body. <b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.	<a href="#">Response 200</a>
<b>412</b>	Status 412	<a href="#">Response 412</a>

## Response 200

Name	Description	Schema
<b>userDefinedData</b> <i>required</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object

## Response 412

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Get PNFd Content

```
GET /pnf_descriptors/{pnfdInfoId}/pnfd_content
```

### Description

The GET method fetches the content of the PNFd.

### Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non-empty message body.	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
Path	<b>pnfdInfoId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
200	<p>On success, the content of the PNFD is returned. The payload body shall contain a copy of the file representing the PNFD. The "Content-Type" HTTP header shall be set to "text/plain".</p> <p><b>Headers :</b></p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p> <p><b>Content-Type</b> (string) : The "Content-Type" HTTP header shall be set to "text/plain".</p>	No Content

## Upload PNFD

```
PUT /pnf_descriptors/{pnfdInfoId}/pnfd_content
```

### Description

The PUT method is used to upload the content of a PNFD. This method shall follow the provisions specified in the Tables 5.4.7.3.3-1 and 5.4.7.3.3-2 of GS NFV-SOL 005 for URI query parameters, request and response data structures, and response codes.

### Parameters

Type	Name	Description	Schema
Header	<b>Content-Type</b> <i>optional</i>	The request shall set the "Content-Type" HTTP header to "text/plain".	string

Type	Name	Description	Schema
Path	<b>pnfdInfoId</b> <i>required</i>		string
Body	<b>body</b> <i>required</i>		object

## Responses

HTTP Code	Description	Schema
204	The PNFD content was successfully uploaded and validated. The response body shall be empty.	No Content
409	Status 409	<a href="#">Response 409</a>

### Response 409

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## Subscribe

POST /subscriptions



## Description

The POST method creates a new subscription. This method shall support the URI query parameters, request and response data structures, and response codes, as specified in the Tables 5.4.8.3.1-1 and 5.4.8.3.1-2 of GS-NFV SOL 005. Creation of two subscription resources with the same callbackURI and the same filter can result in performance degradation and will provide duplicates of notifications to the OSS, and might make sense only in very rare use cases. Consequently, the NFVO may either allow creating a subscription resource if another subscription resource with the same filter and callbackUri already exists (in which case it shall return the "201 Created" response code), or may decide to not create a duplicate subscription resource (in which case it shall return a "303 See Other" response code referencing the existing subscription resource with the same filter and callbackUri).

## Parameters

Type	Name	Description	Schema
Header	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non empty message body.	string
Header	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
Header	<b>Content-Type</b> <i>required</i>	The MIME type of the body of the request. This header field shall be present if the request has a non-empty message body.	string
Body	<b>body</b> <i>required</i>		<a href="#">body</a>

### body

Name	Description	Schema
<b>authentication</b> <i>optional</i>		<a href="#">authentication</a>
<b>callbackUri</b> <i>required</i>	The URI of the endpoint to send the notification to.	string

Name	Description	Schema
<b>filter</b> <i>optional</i>	This type represents a subscription filter related to notifications about NSD management. It shall comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	<a href="#">filter</a>

## authentication

Name	Description	Schema
<b>authType</b> <i>optional</i>	<p>Defines the types of Authentication/ Authorization the API consumer is willing to accept when receiving a notification.</p> <p>Permitted values: BASIC: In every HTTP request to the notification endpoint, use HTTP Basic authentication with the client credentials.</p> <p>OAUTH2_CLIENT_CREDENTIALS: In every HTTP request to the notification endpoint, use an OAuth 2.0 Bearer token, obtained using the client credentials grant type.</p> <p>TLS_CERT: Every HTTP request to the notification endpoint is sent over a mutually authenticated TLS session. i.e. not only server is authenticated, but also the client is authenticated during the TLS tunnel setup.</p>	enum (BASIC, OAUTH2_CLIENT_CREDENTIALS, TLS_CERT)
<b>paramsBasic</b> <i>optional</i>	Parameters for authentication/authorization using BASIC. Shall be present if authType is "BASIC" and the contained information has not been provisioned out of band. Shall be absent otherwise.	<a href="#">paramsBasic</a>
<b>paramsOauth2ClientCredentials</b> <i>optional</i>	Parameters for authentication/authorization using OAUTH2_CLIENT_CREDENTIALS. Shall be present if authType is "OAUTH2_CLIENT_CREDENTIALS" and the contained information has not been provisioned out of band. Shall be absent otherwise.	<a href="#">paramsOauth2ClientCredentials</a>

## paramsBasic

Name	Description	Schema
<b>password</b> <i>optional</i>	Password to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string
<b>userName</b> <i>optional</i>	Username to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string

### paramsOauth2ClientCredentials

Name	Description	Schema
<b>clientId</b> <i>optional</i>	Client identifier to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band.	string

### filter

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array

Name	Description	Schema
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## Responses

HTTP Code	Description	Schema
201	<p>Status 201</p> <p><b>Headers :</b></p> <p><b>Location</b> (string) : The HTTP response shall include a "Location:" HTTP header that points to the created subscription resource.</p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	<a href="#">Response 201</a>

### Response 201

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>callbackUri</b> <i>required</i>	String formatted according to IETF RFC 3986 [10].	object
<b>filter</b> <i>optional</i>	This type represents a subscription filter related to notifications about NSD management. It shall comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	<a href="#">filter</a>
<b>id</b> <i>required</i>	Identifier of this subscription resource	string

### [\\_links](#)

Name	Description	Schema
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **filter**

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array

Name	Description	Schema
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array



Name	Description	Schema
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## Query Subscription Information

GET /subscriptions

### Description

The GET method queries the list of active subscriptions of the functional block that invokes the method. It can be used e.g. for resynchronization after error situations. This method shall support the URI query parameters, request and response data structures, and response codes, as specified in the Tables 5.4.8.3.2-1 and 5.4.8.3.2-2 of GS NFV-SOL 005.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non empty message body.	string
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string

### Responses

HTTP Code	Description	Schema
200	<p>Status 200</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	< <a href="#">Response 200</a> > array
303	<p>A subscription with the same callbackURI and the same filter already exists and the policy of the NFVO is to not create redundant subscriptions. The response body shall be empty.</p> <p><b>Headers :</b></p> <p><b>Location</b> (string) : The HTTP response shall include a "Location" HTTP header that contains the resource URI of the existing subscription resource.</p>	No Content

### Response 200

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>callbackUri</b> <i>required</i>	String formatted according to IETF RFC 3986 [10].	object
<b>filter</b> <i>optional</i>	This type represents a subscription filter related to notifications about NSD management. It shall comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	<a href="#">filter</a>
<b>id</b> <i>required</i>	Identifier of this subscription resource	string

### [\\_links](#)

Name	Description	Schema
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### filter

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array

Name	Description	Schema
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array

Name	Description	Schema
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## Query Subscription Information

```
GET /subscriptions/{subscriptionId}
```

### Description

The GET method retrieves information about a subscription by reading an individual subscription resource. This method shall support the URI query parameters, request and response data structures, and response codes, as specified in the Tables 5.4.9.3.2-1 and 5.4.9.3.2-2.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Accept</b> <i>required</i>	Content-Types that are acceptable for the response. This header field shall be present if the response is expected to have a non empty message body.	string
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string

Type	Name	Description	Schema
Path	<b>subscriptionId</b> <i>required</i>		string

## Responses

HTTP Code	Description	Schema
200	<p>Status 200</p> <p><b>Headers :</b></p> <p><b>Content-Type</b> (string) : The MIME type of the body of the response. This header field shall be present if the response has a non-empty message body.</p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	<a href="#">Response 200</a>

### Response 200

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>callbackUri</b> <i>required</i>	String formatted according to IETF RFC 3986 [10].	object
<b>filter</b> <i>optional</i>	This type represents a subscription filter related to notifications about NSD management. It shall comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	<a href="#">filter</a>
<b>id</b> <i>required</i>	Identifier of this subscription resource	string

[\\_links](#)

Name	Description	Schema
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### filter

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array



Name	Description	Schema
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## Terminate Subscription

```
DELETE /subscriptions/{subscriptionId}
```

### Description

The DELETE method terminates an individual subscription. This method shall support the URI query parameters, request and response data structures, and response codes, as specified in the Tables 5.4.9.3.5-1 and 5.4.9.3.3-2 of GS NFV-SOL 005.

### Parameters

Type	Name	Description	Schema
<b>Header</b>	<b>Authorization</b> <i>optional</i>	The authorization token for the request. Details are specified in clause 4.5.3 of GS NFV-SOL 005.	string
<b>Path</b>	<b>subscriptionId</b> <i>required</i>		string

### Responses

HTTP Code	Description	Schema
204	<p>The subscription resource was deleted successfully. The response body shall be empty.</p> <p><b>Headers :</b></p> <p><b>WWW-Authenticate</b> (string) : Challenge if the corresponding HTTP request has not provided authorization, or error details if the corresponding HTTP request has provided an invalid authorization token.</p>	No Content

## Definitions

### CreateNsdInfoRequest

This type creates a completely new NS descriptor resource.

Name	Description	Schema
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object

### CreatePnfdInfoRequest

This type creates a new PNF descriptor resource.

Name	Description	Schema
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object

## KeyValuePairs

This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].

*Type* : object

# Link

This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.

Type : object

# NsdChangeNotification

This type represents an NSD management notification, which informs the receiver of a change of the "nsdOperationalState" attribute of an on-boarded NSD. Changes in the value of the "nsdUsageState" and "nsdOnboardingState" attributes are not reported. The notification shall comply with the provisions defined in Table 5.5.2.11-1 of GS NFV-SOL 005. The support of this notification is mandatory. The notification shall be triggered by the NFVO when the value of the "nsdOperationalState" attribute has changed, and the "nsdOperationalState" attribute has the value "ONBOARDED".

Name	Description	Schema
<b>_links</b> <i>required</i>	This type represents the links to resources that an NSD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "NsdChangeNotification" for this notification type.	string
<b>nsdId</b> <i>required</i>	This identifier, which is managed by the service provider, identifies the NSD in a globally unique way. It is copied from the on-boarded NSD.	string
<b>nsdInfoId</b> <i>required</i>	Identifier of the NSD information object. This identifier is allocated by the NFVO.	string
<b>nsdOperationalState</b> <i>required</i>	<p>The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV_SOL 005. It indicates the operational state of the resource.</p> <p>ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.</p>	enum (ENABLED, DISABLED)

Name	Description	Schema
<b>subscriptionId</b> <i>required</i>	Identifier of the subscription that this notification relates to.	string
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### links

Name	Description	Schema
<b>nsdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## NsdDeletionNotification

This type represents an NSD management notification, which informs the receiver of the deletion of an on-boarded NSD. The notification shall comply with the provisions defined in Table 5.5.2.12-1. The support of this notification is mandatory. The notification shall be triggered by the NFVO when it has deleted an on-boarded NSD.

Name	Description	Schema
<b><u>links</u></b> <i>required</i>	This type represents the links to resources that an NSD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "NsdDeletionNotification " for this notification type.	string
<b>nsdId</b> <i>required</i>	This identifier, which is managed by the service provider, identifies the NSD in a globally unique way. It is copied from the on-boarded NSD.	string

Name	Description	Schema
<b>nsdInfoId</b> <i>required</i>	Identifier of the NSD information object. This identifier is allocated by the NFVO.	string
<b>subscriptionId</b> <i>required</i>	Identifier of the subscription that this notification relates to.	string
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### links

Name	Description	Schema
<b>nsdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## NsdInfo

This type represents a response for the query NSD operation. It shall comply with the provisions defined in Table 5.5.2.2-1 of GS NFV-SOL 005.

Name	Description	Schema
<b><u>links</u></b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of the onboarded individual NS descriptor resource. This identifier is allocated by the NFVO.	string
<b>nestedNsdInfoIds</b> <i>optional</i>	Identifies the NsdInfo element for the nested NSD referenced by the on-boarded NS descriptor resource. At least one of the attributes – vnfPkgId and nestedNsdInfoId shall be present, after the NSD is on-boarded.	< string > array
<b>nsdDesigner</b> <i>optional</i>	Designer of the on-boarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string

Name	Description	Schema
<b>nsdId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies the NSD in a globally unique way. It is copied from the NSD content and shall be present after the NSD content is on-boarded.	object
<b>nsdInvariantId</b> <i>optional</i>	This identifier, which is allocated by the NSD designer, identifies an NSD in a version independent manner. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdName</b> <i>optional</i>	Name of the onboarded NSD. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string
<b>nsdOnboardingState</b> <i>required</i>	The enumeration NsdOnboardingStateType shall comply with the provisions defined in Table 5.5.4.5-1 of GS NFV-SOL 005. It indicates the onboarding state of the NSD.  CREATED = The NSD information object is created. UPLOADING = The associated NSD content is being uploaded. PROCESSING = The associated NSD content is being processed, e.g. validation. ONBOARDED = The associated NSD content is on-boarded.	enum (CREATED, UPLOADING, PROCESSING, ONBOARDED)
<b>nsdOperationalState</b> <i>required</i>	The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV-SOL 005. It indicates the operational state of the resource.  ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.	enum (ENABLED, DISABLED)
<b>nsdUsageState</b> <i>required</i>	The enumeration NsdUsageStateType shall comply with the provisions defined in Table 5.5.4.4-1 of GS NFV-SOL 005. It indicates the usage state of the resource.  IN_USE = The resource is in use. NOT_IN_USE = The resource is not-in-use.	enum (IN_USE, NOT_IN_USE)
<b>nsdVersion</b> <i>optional</i>	Version of the on-boarded NSD. The NSD version is a string of variable length. This information is copied from the NSD content and shall be present after the NSD content is on-boarded.	string

Name	Description	Schema
<b>onboardingFailureDetails</b> <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>
<b>pnfdInfoIds</b> <i>optional</i>	Identifies the PnfdInfo element for the PNFD referenced by the on-boarded NS descriptor resource.	< string > array
<b>userDefinedData</b> <i>optional</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object
<b>vnfPkgIds</b> <i>optional</i>	Identifies the VNF package for the VNFD referenced by the on-boarded NS descriptor resource.	< string > array

### links

Name	Description	Schema
<b>nsd_content</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **onboardingFailureDetails**

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## NsdInfoModifications

This type represents attribute modifications for an individual NS descriptor resource based on the "NsdInfo" data type. The attributes of "NsdInfo" that can be modified are included in the "NsdInfoModifications" data type.

**NOTE** At least one of the attributes - nsdOperationalState and userDefinedData - shall be present.

Name	Description	Schema
<b>nsdOperationalState</b> <i>optional</i>	The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV_SOL 005. It indicates the operational state of the resource.  ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.	enum (ENABLED, DISABLED)
<b>userDefinedData</b> <i>optional</i>	Modifications of the "userDefinedData" attribute in "NsdInfo" data type. See note. If present, these modifications shall be applied according to the rules of JSON Merge PATCH (see IETF RFC 7396 [25]). NOTE: At least one of the attributes - nsdOperationalState and userDefinedData - shall be present.	object



# NsdOnboardingFailureNotification

This type represents an NSD management notification, which informs the receiver of the failure of on-boarding an NSD. It shall comply with the provisions defined in Table 5.5.2.10-1. The support of this notification is mandatory. The notification shall be triggered by the NFVO when the on-boarding of an NSD has failed.

Name	Description	Schema
<b>_links</b> <i>required</i>	This type represents the links to resources that an NSD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "NsdOnboardingFailureNotification" for this notification type.	string
<b>nsdId</b> <i>optional</i>	This identifier, which is managed by the service provider, identifies the NSD in a globally unique way.	string
<b>nsdInfoId</b> <i>required</i>	Identifier of the NSD information object. This identifier is allocated by the NFVO.	string
<b>onboardingFailureDetails</b> <i>required</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>

Name	Description	Schema
<b>subscriptionId</b> <i>optional</i>	Identifier of the subscription that this notification relates to.	string
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### links

Name	Description	Schema
<b>nsdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **onboardingFailureDetails**

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## **NsdOnboardingNotification**

This type represents an NSD management notification, which informs the receiver of the successful

on-boarding of an NSD. It shall comply with the provisions defined in Table 5.5.2.9-1 of GS NFV-SOL 005. The support of this notification is mandatory. The notification shall be triggered by the NFVO when the "nsdOnboardingState" attribute of a new NSD has changed to "ONBOARDED".

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b><u>links</u></b> <i>required</i>	This type represents the links to resources that an NSD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "NsdOnboardingNotification" for this notification type.	string
<b>nsdId</b> <i>required</i>	This identifier, which is managed by the service provider, identifies the NSD in a globally unique way. It is copied from the on-boarded NSD.	string
<b>nsdInfoId</b> <i>required</i>	Identifier of the NSD information object. This identifier is allocated by the NFVO.	string
<b>subscriptionId</b> <i>required</i>	Identifier of the subscription that this notification relates to.	string
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### links

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>nsdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## NsdOnboardingStateType

The enumeration NsdOnboardingStateType shall comply with the provisions defined in Table 5.5.4.5-1 of GS NFV-SOL 005. It indicates the onboarding state of the NSD.

CREATED = The NSD information object is created. UPLOADING = The associated NSD content is being uploaded. PROCESSING = The associated NSD content is being processed, e.g. validation. ONBOARDED = The associated NSD content is on-boarded.

Type : enum (CREATED, UPLOADING, PROCESSING, ONBOARDED)

## NsdOperationalStateType

The enumeration NsdOperationalStateType shall comply with the provisions defined in Table 5.5.4.3-1 of GS NFV\_SOL 005. It indicates the operational state of the resource.

ENABLED = The operational state of the resource is enabled. DISABLED = The operational state of the resource is disabled.

Type : enum (ENABLED, DISABLED)

## NsdUsageStateType

The enumeration NsdUsageStateType shall comply with the provisions defined in Table 5.5.4.4-1 of GS NFV-SOL 005. It indicates the usage state of the resource.

IN\_USE = The resource is in use. NOT\_IN\_USE = The resource is not-in-use.

Type : enum (IN\_USE, NOT\_IN\_USE)

## NsdmLinks

This type represents the links to resources that an NSD management notification can contain.

Name	Description	Schema
<b>nsdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## NsdmNotificationsFilter

This type represents a subscription filter related to notifications about NSD management. It shall

comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array

<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array

Name	Description	Schema
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## NsdmSubscription

This type represents a subscription related to notifications about NSD management.

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>callbackUri</b> <i>required</i>	String formatted according to IETF RFC 3986 [10].	object
<b>filter</b> <i>optional</i>	This type represents a subscription filter related to notifications about NSD management. It shall comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	<a href="#">filter</a>
<b>id</b> <i>required</i>	Identifier of this subscription resource	string

[\\_links](#)

Name	Description	Schema
<b>self</b> <i>optional</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### filter

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array



<b>Name</b>	<b>Description</b>	<b>Schema</b>
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array

Name	Description	Schema
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## NsdmSubscriptionRequest

This type represents a subscription request related to notifications about NSD management.

Name	Description	Schema
<b>authentication</b> <i>optional</i>		<a href="#">authentication</a>
<b>callbackUri</b> <i>required</i>	The URI of the endpoint to send the notification to.	string
<b>filter</b> <i>optional</i>	This type represents a subscription filter related to notifications about NSD management. It shall comply with the provisions defined in Table 5.5.3.2-1 of GS NFV-SOL 005. At a particular nesting level in the filter structure, the following applies: All attributes shall match in order for the filter to match (logical "and" between different filter attributes). If an attribute is an array, the attribute shall match if at least one of the values in the array matches (logical "or" between the values of one filter attribute).	<a href="#">filter</a>

**authentication**

Name	Description	Schema
<b>authType</b> <i>optional</i>	<p>Defines the types of Authentication/ Authorization the API consumer is willing to accept when receiving a notification.</p> <p>Permitted values: BASIC: In every HTTP request to the notification endpoint, use HTTP Basic authentication with the client credentials.</p> <p>OAUTH2_CLIENT_CREDENTIALS: In every HTTP request to the notification endpoint, use an OAuth 2.0 Bearer token, obtained using the client credentials grant type.</p> <p>TLS_CERT: Every HTTP request to the notification endpoint is sent over a mutually authenticated TLS session. i.e. not only server is authenticated, but also the client is authenticated during the TLS tunnel setup.</p>	enum (BASIC, OAUTH2_CLIENT_CREDENTIALS, TLS_CERT)
<b>paramsBasic</b> <i>optional</i>	Parameters for authentication/authorization using BASIC. Shall be present if authType is "BASIC" and the contained information has not been provisioned out of band. Shall be absent otherwise.	<a href="#">paramsBasic</a>
<b>paramsOauth2ClientCredentials</b> <i>optional</i>	Parameters for authentication/authorization using OAUTH2_CLIENT_CREDENTIALS. Shall be present if authType is "OAUTH2_CLIENT_CREDENTIALS" and the contained information has not been provisioned out of band. Shall be absent otherwise.	<a href="#">paramsOauth2ClientCredentials</a>

### paramsBasic

Name	Description	Schema
<b>password</b> <i>optional</i>	Password to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string
<b>userName</b> <i>optional</i>	Username to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string

### paramsOauth2ClientCredentials

Name	Description	Schema
<b>clientId</b> <i>optional</i>	Client identifier to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band.	string

### filter

Name	Description	Schema
<b>nestedNsdInfoIds</b> <i>optional</i>	Match the NsdInfo identifier for the nested NSD referenced by the on-boarded NSD.	< string > array
<b>notificationTypes</b> <i>optional</i>	<p>Match particular notification types. Permitted values: NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification.</p> <p>The permitted values of the "notificationTypes" attribute are spelled exactly as the names of the notification types to facilitate automated code generation systems.</p>	< enum (NsdOnBoardingNotification, NsdOnboardingFailureNotification, NsdChangeNotification, NsdDeletionNotification, PnfdOnBoardingNotification, PnfdOnBoardingFailureNotification, PnfdDeletionNotification) > array
<b>nsdDesigner</b> <i>optional</i>	Match the NSD designer of the on-boarded NSD.	< string > array
<b>nsdId</b> <i>optional</i>	Match the NSD identifier, which is allocated by the NSD designer. The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInfoId</b> <i>optional</i>	Match the NsdInfo identifier which is allocated by the NFVO. Note: The attributes "nsdId" and "nsdInfoId" are alternatives to reference to a particular NSD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>nsdInvariantId</b> <i>optional</i>	Match the NSD invariant identifier which is allocated by the NSD designer and identifies an NSD in a version independent manner.	< string > array
<b>nsdName</b> <i>optional</i>	Match the name of the onboarded NSD.	< string > array

Name	Description	Schema
<b>nsdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDED) > array
<b>nsdOperationalState</b> <i>optional</i>		< enum (ENABLED, DISABLED) > array
<b>nsdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>nsdVersion</b> <i>optional</i>	Match the NSD version listed as part of this attribute. The NSD version is a string of variable length.	< string > array
<b>pnfdId</b> <i>optional</i>	Match the PNFD identifier which is copied from the PNFD content. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInfoIds</b> <i>optional</i>	Match the PnfdInfo identifier for the PNFD referenced by the on-boarded NSD. The attributes "pnfdId" and "pnfdInfoId" are alternatives to reference to a particular PNFD in a filter. They should not be used both in the same filter instance, but one alternative should be chosen.	< string > array
<b>pnfdInvariantId</b> <i>optional</i>	Match the PNFD in a version independent manner.	< string > array
<b>pnfdName</b> <i>optional</i>	Match the name of the on-boarded PNFD.	< string > array
<b>pnfdOnboardingState</b> <i>optional</i>		< enum (CREATED, UPLOADING, PROCESSING, ONBOARDING) > array
<b>pnfdProvider</b> <i>optional</i>	Match the provider of the on-boarded PNFD.	< string > array

Name	Description	Schema
<b>pnfdUsageState</b> <i>optional</i>		< enum (IN_USE, NOT_IN_USE) > array
<b>pnfdVersion</b> <i>optional</i>	Match the PNFD designer of the on-boarded PNFD. The PNFD version is a string of variable length.	< string > array
<b>vnfPkgIds</b> <i>optional</i>	Match VNF packages with a package identifier listed in the attribute.	< string > array

## PnfdDeletionNotification

This type represents a PNFD management notification, which informs the receiver of the deletion of an on-boarded PNFD. The notification shall comply with the provisions defined in Table 5.5.2.15-1. The support of this notification is mandatory. The notification is triggered when an on-boarded PNFD is deleted.

Name	Description	Schema
<b>_links</b> <i>required</i>	This type represents the links to resources that a PNFD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "PnfdDeletionNotification " for this notification type.	string
<b>pnfdId</b> <i>required</i>	This identifier, which is managed by the service provider, identifies the PNFD in a globally unique way. It is copied from the on-boarded PNFD.	string
<b>pnfdInfoId</b> <i>required</i>	Identifier of the PNFD information object. This identifier is allocated by the NFVO.	string
<b>subscriptionId</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string

Name	Description	Schema
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### **\_links**

Name	Description	Schema
<b>pnfdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## **PnfdInfo**

This type represents a response for the query PNF operation.

Name	Description	Schema
<b>_links</b> <i>required</i>	Links to resources related to this resource.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of the onboarded individual PNF descriptor resource. This identifier is allocated by the NFVO.	string
<b>onboardingFailureDetails</b> <i>optional</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>

Name	Description	Schema
<b>pnfdId</b> <i>optional</i>	This identifier, which is managed by the PNFD designer, identifies the PNFD in a globally unique way. It is copied from the PNFD content and shall be present after the PNFD content is on-boarded.	string
<b>pnfdInvariantId</b> <i>optional</i>	Identifies a PNFD in a version independent manner. This attribute is invariant across versions of PNFD.	string
<b>pnfdName</b> <i>optional</i>	Name of the onboarded PNFD. This information is copied from the PNFD content and shall be present after the PNFD content is on-boarded.	string
<b>pnfdOnboardingState</b> <i>required</i>	<p>The enumeration PnfdOnboardingStateType shall comply with the provisions defined in Table 5.5.4.6-1 of GS-NFV SOL005. It indicates the onboarding state of the individual PNF descriptor resource.</p> <p>CREATED = The PNF descriptor resource is created.          UPLOADING = The associated PNFD content is being uploaded.          PROCESSING = The associated PNFD content is being processed, e.g. validation.          ONBOARDED = The associated PNFD content is on-boarded.</p>	enum (CREATED, UPLOADING, PROCESSING, ONBOARDING)
<b>pnfdProvider</b> <i>optional</i>	Provider of the onboarded PNFD. This information is copied from the PNFD content and shall be present after the PNFD content is onboarded.	string
<b>pnfdUsageState</b> <i>required</i>	<p>The enumeration PnfdUsageStateType shall comply with the provisions defined in Table 5.5.4.7-1 of GS NFV-SOL005. It indicates the usage state of the resource.</p> <p>IN-USE = The resource is in use. NOT_IN_USE = The resource is not-in-use.</p>	enum (IN_USE, NOT_IN_USE)
<b>pnfdVersion</b> <i>optional</i>	Version of the onboarded PNFD. The PNFD version is a string of variable length. This information is copied from the PNFD content and shall be present after the PNFD content is on-boarded.	string
<b>userDefinedData</b> <i>optional</i>	User defined data for the individual PNF descriptor resource. This attribute can be modified with the PATCH method.	< object > array

**links**



Name	Description	Schema
<b>pnfd_content</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>self</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### onboardingFailureDetails

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## PnfdInfoModifications

This type represents attribute modifications for an individual PNF descriptor resource based on the "PnfdInfo" data type. The attributes of "PnfdInfo" that can be modified are included in the "PnfdInfoModifications" data type.

Name	Description	Schema
<b>userDefinedData</b> <i>required</i>	This type represents a list of key-value pairs. The order of the pairs in the list is not significant. In JSON, a set of keyvalue pairs is represented as an object. It shall comply with the provisions defined in clause 4 of IETF RFC 7159 [20].	object

# PnfdOnboardingFailureNotification

This type represents a PNFD management notification, which informs the receiver of the failure of on-boarding a PNFD. It shall comply with the provisions defined in Table 5.5.2.14-1 of GS NFV-SOL 005. The support of this notification is mandatory. The notification is triggered when the on-boarding of a PNFD fails.

Name	Description	Schema
<b>_links</b> <i>required</i>	This type represents the links to resources that a PNFD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "PnfdOnboardingFailureNotification" for this notification type.	string
<b>onboardingFailureDetails</b> <i>required</i>	<p>The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.</p> <p>The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].</p>	<a href="#">onboardingFailureDetails</a>
<b>pnfdId</b> <i>optional</i>	This identifier, which is managed by the service provider, identifies the PNFD in a globally unique way.	string
<b>pnfdInfoId</b> <i>required</i>	Identifier of the PNFD information object. This identifier is allocated by the NFVO.	string

Name	Description	Schema
<b>subscriptionId</b> <i>required</i>	Identifier of the subscription that this notification relates to.	string
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### links

Name	Description	Schema
<b>pnfdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

### **onboardingFailureDetails**

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## **PnfdOnboardingNotification**

This type represents a PNFD management notification, which informs the receiver of the successful

on-boarding of a PNFD. It shall comply with the provisions defined in Table 5.5.2.13-1. The support of this notification is mandatory. The notification is triggered when a new PNFD is on-boarded.

Name	Description	Schema
<b>_links</b> <i>required</i>	This type represents the links to resources that a PNFD management notification can contain.	<a href="#">_links</a>
<b>id</b> <i>required</i>	Identifier of this notification. If a notification is sent multiple times due to multiple subscriptions, the "id" attribute of all these notifications shall have the same value.	string
<b>notificationType</b> <i>required</i>	Discriminator for the different notification types. Shall be set to "PnfdOnboardingNotification" for this notification type.	string
<b>pnfdId</b> <i>required</i>	This identifier, which is managed by the service provider, identifies the PNFD in a globally unique way. It is copied from the on-boarded PNFD.	string
<b>pnfdInfoId</b> <i>required</i>	Identifier of the PNFD information object. This identifier is allocated by the NFVO.	string
<b>subscriptionId</b> <i>required</i>	Identifier of the subscription that this notification relates to.	string
<b>timeStamp</b> <i>required</i>	Date-time of the generation of the notification.	string (date-time)

### \_links

Name	Description	Schema
<b>pnfdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## PnfdOnboardingStateType

The enumeration PnfdOnboardingStateType shall comply with the provisions defined in Table

5.5.4.6-1 of GS-NFV SOL005. It indicates the onboarding state of the individual PNF descriptor resource.

CREATED = The PNF descriptor resource is created. UPLOADING = The associated PNFD content is being uploaded. PROCESSING = The associated PNFD content is being processed, e.g. validation. ONBOARDED = The associated PNFD content is on-boarded.

Type : enum (CREATED, UPLOADING, PROCESSING, ONBOARDING)

## PnfdUsageStateType

The enumeration PnfdUsageStateType shall comply with the provisions defined in Table 5.5.4.7-1 of GS NFV-SOL005. It indicates the usage state of the resource.

IN-USE = The resource is in use. NOT\_IN\_USE = The resource is not-in-use.

Type : enum (IN\_USE, NOT\_IN\_USE)

## PnfdmLinks

This type represents the links to resources that a PNFD management notification can contain.

Name	Description	Schema
<b>pnfdInfo</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object
<b>subscription</b> <i>required</i>	This type represents a link to a resource. It shall comply with the provisions defined in Table 4.4.1.3-1 of GS NFV-SOL 005.	object

## ProblemDetails

The definition of the general "ProblemDetails" data structure from IETF RFC 7807 [27] is reproduced in Table 4.3.5.3-1 of GS NFV-SOL 005. Compared to the general framework defined in IETF RFC 7807 [27], the "status" and "detail" attributes are mandated to be included by the present document, to ensure that the response contains additional textual information about an error. IETF RFC 7807 [27] foresees extensibility of the "ProblemDetails" type. It is possible that particular APIs in the present document, or particular implementations, define extensions to define additional attributes that provide more information about the error.

The description column only provides some explanation of the meaning to facilitate understanding of the design. For a full description, see IETF RFC 7807 [27].

Name	Description	Schema
<b>detail</b> <i>required</i>	A human-readable explanation specific to this occurrence of the problem.	string
<b>instance</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object
<b>status</b> <i>required</i>	The HTTP status code for this occurrence of the problem.	integer
<b>title</b> <i>optional</i>	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem, except for purposes of localization. If type is given and other than "about:blank", this attribute shall also be provided.	string
<b>type</b> <i>optional</i>	String formatted according to IETF RFC 3986 [10].	object

## SubscriptionAuthentication

Name	Description	Schema
<b>authType</b> <i>optional</i>	<p>Defines the types of Authentication/ Authorization the API consumer is willing to accept when receiving a notification.</p> <p>Permitted values: BASIC: In every HTTP request to the notification endpoint, use HTTP Basic authentication with the client credentials.</p> <p>OAUTH2_CLIENT_CREDENTIALS: In every HTTP request to the notification endpoint, use an OAuth 2.0 Bearer token, obtained using the client credentials grant type.</p> <p>TLS_CERT: Every HTTP request to the notification endpoint is sent over a mutually authenticated TLS session. i.e. not only server is authenticated, but also the client is authenticated during the TLS tunnel setup.</p>	enum (BASIC, OAUTH2_CLIENT_CREDENTIALS, TLS_CERT)
<b>paramsBasic</b> <i>optional</i>	Parameters for authentication/authorization using BASIC. Shall be present if authType is "BASIC" and the contained information has not been provisioned out of band. Shall be absent otherwise.	<a href="#">paramsBasic</a>

Name	Description	Schema
<b>paramsOauth2ClientCredentials</b> <i>optional</i>	Parameters for authentication/authorization using OAUTH2_CLIENT_CREDENTIALS. Shall be present if authType is "OAUTH2_CLIENT_CREDENTIALS" and the contained information has not been provisioned out of band. Shall be absent otherwise.	<a href="#">paramsOauth2ClientCredentials</a>

### paramsBasic

Name	Description	Schema
<b>password</b> <i>optional</i>	Password to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string
<b>userName</b> <i>optional</i>	Username to be used in HTTP Basic authentication. Shall be present if it has not been provisioned out of band.	string

### paramsOauth2ClientCredentials

Name	Description	Schema
<b>clientId</b> <i>optional</i>	Client identifier to be used in the access token request of the OAuth 2.0 client credentials grant type. Shall be present if it has not been provisioned out of band.	string

## Uri

String formatted according to IETF RFC 3986 [10].

Type : object